

Minutes

Of the meeting of the:

Strathfield Local Planning Panel Meeting

Held on:

Thursday, 1 March 2018

Commencing at 10:30am at Council Town Hall (Supper Room), 65 Homebush Road, Strathfield

TABLE OF CONTENTS

Item	Page No.
SLPP AGENDA ITEMS	
SLPP - Report No. 1 DA2017/101- 37-39 Punchbowl Road & 90 Water Street, Belfield LOT 5 DP 7675.....	4
SLPP - Report No. 2 (S82A) DA2017/070/01- 88 Homebush Road, Strathfield Lot 1 DP 309287	40
SLPP - Report No. 3 DA2017/162- 72-73 The Crescent, Homebush Lot 5 in DP 6479	42
SLPP - Report No. 4 DA2017/187- 5 Elva Street, Strathfield Lot 4 DP 302827	69

The meeting of the Strathfield Local Planning Panel Meeting was held in the Council Town Hall (Supper Room), 65 Homebush Road, Strathfield on Thursday 1 March 2018. The meeting commenced at 10:30am.

PRESENT

The Hon Paul Stein QC AM – Chair
Brian Kirk- Expert
Vivienne Albin- Expert
Peter Smith- Community

ALSO PRESENT

Stephen Clements, Director Infrastructure, Development and Environment
Kevin Lee, Planning Officer
Valentina Gorgioski, Administration Assistant
Lily Lam, Administration Assistant

DECLARATIONS OF PECUNIARY INTEREST / CONFLICT OF INTEREST

Nil

TO: Strathfield Local Planning Panel Meeting - 1 March 2018
REPORT: SLPP – Report No. 1
SUBJECT: DA2017/101- 37-39 PUNCHBOWL ROAD & 90 WATER STREET, BELFIELD
LOT 5 DP 7675
DA NO. DA2017/101

RECOMMENDATION

In consideration of the written request made by the applicant pursuant to Clause 4.6 of the Strathfield Local Environmental Plan 2012, the consent authority is satisfied that the noncompliance with the development standard contained in Clause 4.3 (Height of Buildings) of the SLEP 2012 is well founded and that there are sufficient environmental planning grounds to justify contravening the development standard.

That Development Application No. 2017/101 for Demolition of all existing structures on the site, construction of eight (8) storey mixed use development comprising 61 residential apartments, 270m² of commercial/retail floor space at ground floor and three (3) storeys of basement car parking at 37-39 Punchbowl Road, Belfield and 90 Water Street Belfield be granted a **DEFERRED COMMENCEMENT**, subject to the following conditions:

DEFERRED COMMENCEMENT CONDITIONS

DEFERRED COMMENCEMENT APPROVAL

This is a Deferred Commencement Consent under Section 80(3) of the Environmental Planning and Assessment (EP&A Act, 1979. This consent does not become operative until the applicant has satisfied the conditions listed under Schedule A below. All conditions shall be satisfactorily resolved within a period of twelve (12) months from the Determination Date that is shown on this consent. Upon compliance with the conditions under SCHEDULE A and written confirmation of this from Council, the consent shall become operative from the 'Date of Endorsement' (to be included on the written notice of determination).

(Reason: A deferred commencement consent stipulates conditions that must be satisfied before the consent operates in accordance with Section 80(3) of the EP&A Act 1979)

SCHEDULE A

D1 WASTE MANAGEMENT

Amended plans shall be prepared and submitted to Council for approval demonstrating that the following have been provided:

- a. Adequate space has been provided to the ground floor temporary holding bay and level 1 basement to accommodate 11 x 660L general waste bins and 31 x 240L recycling bins;
- b. A minimum 36m² residential garbage room shall be provided in the level 1 basement;
- c. A minimum 24.4m² bulky store room shall be provided in the level 1 basement;
- d. The ground floor waste vehicle standing area shall be allocated with a minimum 12m length, 3.6m height clearance and 3.6m width;
- e. The waste collection area shall be clearly identified on the plans;
- f. Evidence is provided showing that the waste collection vehicles must not impede access to, within or from the site for other users

(Reason: to ensure compliance with Part H of the SCDCP 2005)

D2 ON-SITE PARKING

Amended plans shall be prepared and submitted to Council for approval demonstrating that the following changes have been made:

- a. The basement level 1 car parking is capable of allowing a turning radius available for commercial vehicles accessing the load dock after the ramp;
- b. The column between the visitor space and the ramp be relocated so as not to interrupt vehicular flow;
- c. The space for the commercial vehicle loading dock be reconfigured to as to accommodate a commercial floor space as per Australian Standards; and
- d. The clearance height for the basement be increased to 3.5m as per AS 2890.2 (off-street commercial vehicle facilities).

D3 SITE REMEDIATION

This consent is not to operate until the site has been remediated and validated by an appropriately qualified land contamination consultant to the requirements of the NSW Environment Protection Authority and to the standard acceptable for residential development; and

The Council is furnished with a Site Audit Statement completed and signed by an accredited site auditor under the Contaminated Land Management Act, 1997 which clearly states that the land is suitable for the proposed residential development, without the need for any further remediation or testing.

SPECIAL CONDITIONS (SC)

1. SILVER LEVEL UNIVERSAL DESIGN (SC)

A minimum (20%) apartments to the building shall achieve the Livable Housing Guideline's silver level universal design features as per Part 4Q of the Apartment Design Guide. Plans demonstrating compliance with this requirement shall be submitted and approved by a Private Certifying Authority **prior to the issue of a Construction Certificate.**

(Reason: Comply with the ADG)

2. BASEMENT PARKING (SC)

Amended plans shall be prepared and submitted to a Private Certifying Authority for approval demonstrating compliance with the following:

- A minimum one (1) surplus carparking space shall be allocated as an additional visitor parking space so as to achieve a minimum (13) spaces are required by the ADG;
- A minimum six (6) motorcycle spaces are to be provided in the basement;
- Where there are stacked parking spaces provided in the basement, they shall be allocated to the same unit and clearly indicated as part of any future strata subdivision of the site.

(Reason: Provide sufficient on-site parking for the site)

3. WATER NSW (SC)

- A Water Supply Work Approval from WaterNSW must be obtained prior to commencing dewatering activity on the proposed site. Please complete an Application for approval for water supply works, and/or water use.

- An application for a Water Supply Works Approval will only be accepted upon receipt of supporting documentation, and payment of the applicable fee (see Application fees for New or amended Works and/or Use Approvals). The information required for the processing of the water supply work application may include preparation of a dewatering management plan.
- If approved, the Approval will be issued for a period of up to 24 months to cover the dewatering requirements during the construction phase. It will include conditions to ensure that impacts are acceptable and that adequate monitoring and reporting procedures are carried out. The Approval will be issued subject to the proponent meeting requirements of other agencies and consent authorities. For example, an authorisation by either Sydney Water or the local Council, depending where the water will be discharged. If contaminants are likely, or are found to be present in groundwater, and are being discharged to stormwater, including high salinities, a discharge licence under the *Protection of the Environment Operations Act 1997 (NSW)* may also be required.
- WaterNSW prefers “tanking” (ie. total water proofing below the seasonal high water table) of basement excavations, and avoids the ongoing extraction of groundwater after the initial construction phase. It is also advised to adopt measures to facilitate movement of groundwater post construction (eg. a drainage blanket behind the water-proof membrane).
- If the basement is not “tanked”, the proponent will require a Water Access Licence (WAL) and need to acquire groundwater entitlements equivalent to the yearly ongoing take of groundwater. Please note: Acquiring groundwater entitlements could be difficult, and may cause delay in project completion. If a WAL is required, please complete an Application for a new water access licence with a zero share component.

(Reason: Compliance with Water NSW requirements)

4. **RMS (SC)**

- a. Any new buildings or structures (other than pedestrian footpath awnings), together with any improvements integral to the future use of the site, are erected clear of the land reserved for road widening (unlimited in height or depth). Furthermore, no substantial trees or trees with the potential to be substantial trees are to be planted in the area reserved for road widening.
- b. All vehicular access is to be provided from Water Street at the furthest possible extent from the traffic signals at Punchbowl Road and Water Street.
- c. The layout of the proposed car parking areas associated with the subject development (including, driveways, grades, turn paths, sight distance requirements in relation to landscaping and/or fencing, aisle widths, aisle lengths, and parking bay dimensions) shall be in accordance with AS 2890.1-2004, A52890.6-2009 and AS 2890.2-2002 for heavy vehicle usage.
- d. Construction works zone will not be permitted on Punchbowl Road.

(Reason: compliance with RMS)

5. **AUSGRID (SC)**

Method of Electricity Connection

The method of connection will be in line with Ausgrid's Electrical Standard (ES)1 – 'Premise Connection Requirements.

Supply of Electricity

It is recommended for the nominated electrical consultant/contractor to provide a preliminary enquiry to Ausgrid to obtain advice for the connection of the proposed development to the adjacent electricity network infrastructure. An assessment will be carried out based on the enquiry which may include whether or not:

- The existing network can support the expected electrical load of the development
- A substation may be required on-site, either a pad mount kiosk or chamber style and;
- site conditions or other issues that may impact on the method of supply.

Please direct the developer to Ausgrid's website, www.ausgrid.com.au about how to connect to Ausgrid's network.

Conduit Installation

The need for additional electricity conduits in the footway adjacent to the development will be assessed and documented in Ausgrid's Design Information, used to prepare the connection project design.

Vegetation

All proposed vegetation underneath overhead power lines and above underground cables must comply with the requirements of ISSC 3 Guideline For Managing Vegetation Near Power Lines.

Streetlighting

The developer is to consider the impact that existing streetlighting and any future replacement street lighting and maintenance may have on the development. Should the developer determine that any existing streetlighting may impact the development, the developer should either review the development design, particular the placement of windows, or discuss with Ausgrid the options for relocating the streetlighting. The relocating of any street lighting will generally be at the developers cost. In many cases is not possible to relocate streetlighting due to its strategic positioning.

Service Mains

It appears the existing overhead electricity service mains, that supply the subject property, may not have sufficient clearance to the proposed construction as per the requirements of "The Installation and Service Rules of NSW".

It is recommended that the developer engage a Level 2 Accredited Service Provider (ASP) Electrician to ensure that the installation will comply with the Service Rules.

Proximity to Existing Network Assets Overhead Powerlines

There are existing overhead electricity network assets in Water St & Punchbowl Rd. Safework NSW Document – Work Near Overhead Powerlines: Code of Practice, outlines the minimum safety separation requirements between these mains/poles to structures within the development throughout the construction process. It is a statutory requirement that these distances be maintained throughout construction. Special consideration should be given to the positioning and operating of cranes and the location of any scaffolding.

The "as constructed" minimum clearances to the mains should also be considered. These distances are outlined in the Ausgrid Network Standard, NS220 Overhead Design Manual. This document can be sourced from Ausgrid's website, www.ausgrid.com.au

Before a Construction Certificate is issued, the developer will be required to submit a survey plan to Ausgrid showing the location of all overhead mains within 5 metres of the

proposed development. This drawing must contain a plan view and an elevated view clearly indicating the location of the overhead mains in relation to the development. This information should be forwarded to email address at the top of this letter for further comment.

Should the existing overhead mains require relocating due to the minimum safety clearances being compromised in either of the above scenarios, this relocation work is generally at the developers cost.

It is also the responsibility of the developer to ensure that the existing overhead mains have sufficient clearance from all types of vehicles that are expected be entering and leaving the site.

Underground Cables

There are existing underground electricity network assets in Punchbowl Rd.

Special care should also be taken to ensure that driveways and any other construction activities within the footpath area do not interfere with the existing cables in the footpath. Ausgrid cannot guarantee the depth of cables due to possible changes in ground levels from previous activities after the cables were installed.

Hence it is recommended that the developer locate and record the depth of all known underground services prior to any excavation in the area.

Should ground anchors be required in the vicinity of the underground cables, the anchors must not be installed within 300mm of any cable, and the anchors must not pass over the top of any cable. Safework Australia – Excavation Code of Practice, and Ausgrid’s Network Standard NS156 outlines the minimum requirements for working around Ausgrid’s underground cables.

(Reason: Compliance with Ausgrid)

GENERAL CONDITIONS (GC)

6. APPROVED PLANS AND REFERENCE DOCUMENTATION (GC)

The development, except where modified by a condition(s) of consent, is to be carried out in accordance with the following plans and reference documentation:

Plans affixed with Council’s ‘Development Consent’ stamp relating to Development Consent No. 2017/101:

Drawing No.	Title/Description	Prepared by	Issue / Revision & Date	Date received by Council
DA-003	Site Roof and Demolition Plan	Zhinar Architects	C	30 November 2017
DA-101	Basement 3	Zhinar Architects	C	30 November 2017
DA-102	Basement 2	Zhinar Architects	C	30 November 2017
DA-103	Basement 1	Zhinar Architects	C	30 November 2017
DA-104	Ground Floor Plan	Zhinar Architects	C	30 November 2017
DA-105	Typical Floor Plan L1-L3	Zhinar Architects	C	30 November 2017
DA-106	Floor Plan L4	Zhinar Architects	C	30 November 2017

MINUTES

DA-107	Floor Plan L5	Zhinar Architects	C	30 November 2017
DA-108	Floor Plan L6	Zhinar Architects	C	30 November 2017
DA-109	Floor Plan L7	Zhinar Architects	C	30 November 2017
DA-201	West Elevation - Streetscape	Zhinar Architects	C	30 November 2017
DA-202	East Elevation	Zhinar Architects	C	30 November 2017
DA-203	South Elevation - Streetscape	Zhinar Architects	C	30 November 2017
DA-204	North Elevation	Zhinar Architects	C	30 November 2017
DA-205	Sections	Zhinar Architects	C	30 November 2017
DA-301	Materials Schedule	Zhinar Architects	C	30 November 2017
Sheet 1 of 2	Landscape Site Plan	Paul Scrivener	C	30 November 2017
Sheet 2 of 2	Planting Plan/Calculations Plan	Paul Scrivener	C	30 November 2017
Sheets 1-7 SW001 – SW050	Stormwater Plans	Mance Arraj Civil and Structural Engineers	A	30 November 2017

Reference Documentation affixed with Council's 'Development Consent' stamp relating to Development Consent No. 2017/101:

Title / Description	Prepared by	Issue/Revision & Date	Date received by Council
Statement of Environmental Effects	Caladines Town Planning	November 2017	30 November 2017
Access Report	Vista Access Architects		30 November 2017
Acoustic Report	Sebastian Giglio Acoustic Consultant	Ref: 2833/D05	30 November 2017
Arborist Report	Regum Horticultural	REF: 2812	30 November 2017
BASIX Certificate	-	Cert No: 829246M_03	30 November 2017
Phase 1 Contamination Assessment and Geotechnical Investigation Report	GeoEnviro Consultancy Pty Ltd	June 2017	30 November 2017
Phase 2 Contamination Assessment	GeoEnviro Consultancy Pty Ltd	October 2017	30 November 2017
On-Site Detention Calculation Sheet	Guiseppe Serratore	Job No.2293-C	30 November 2017
Stormwater Quality Management Plan	Mance Arraj	Revision A	4 July 2017

Traffic Report	Varga Traffic Planning Pty LTd	Ref 17140	30 November 2017
Waste Management Plan	-		30 November 2017

In the event of any inconsistency, the conditions of this consent shall prevail.

(Reason: To ensure that the form of the development undertaken is in accordance with the determination of Council.)

7. APPROVAL - SEPARATE APPROVAL REQUIRED (GC)

This consent does not include approval for the fit out and use of the ground floor commercial tenancies on the site. Separate development consent shall be obtained for each of the commercial tenancies on the site.

(Reason: To control future development of the site.)

8. CONSTRUCTION HOURS (GC)

No construction or any other work related activities shall be carried out on the site outside the hours of 7.00 am to 5.00 pm Mondays to Fridays and 8am to 1pm Saturdays.

No building activities are to be carried out at any time on a Sunday or public holiday.

Where the development involves the use of jackhammers/ rock breakers and the like or other heavy machinery, such equipment may only be used between the hours of 7.00 am - 5.00 pm Monday to Friday only.

(Reason: To maintain amenity to adjoining land owners.)

9. CONSTRUCTION WITHIN BOUNDARIES (GC)

The development including but not limited to footings, walls, roof barges and guttering must be constructed wholly within the boundary of the premises. No portion of the proposed structure shall encroach onto the adjoining properties. Gates must be installed so they do not open onto any footpath or adjoining land.

(Reason: Approved works are to be contained wholly within the subject site.)

10. DEMOLITION – GENERALLY (GC)

Alteration and demolition of the existing building is limited to that documented on the approved plans (by way of notation). No approval is given or implied for removal and/or rebuilding of any portion of the existing building which is not shown to be altered or demolished.

(Reason: To ensure compliance with the approved development.)

11. DEMOLITION - SITE SAFETY FENCING (GC)

Site fencing is to be erected to a minimum height of 1.8m complying with WorkCover Guidelines, to exclude public access to the site, prior to any demolition works occurring and maintained for the duration of the demolition works.

If applicable, a separate Hoarding Application for the erection of an A class (fence type) or

B class (overhead type) hoarding along the street frontage(s) complying with WorkCover requirements must be obtained including:

payment to Council of a footpath occupancy fee based on the area of footpath to be occupied and Council's Schedule of Fees and Charges before the commencement of work; and

provision of a Public Risk Insurance Policy with a minimum cover of \$10 million in relation to the occupation of and works within Council's road reserve, for the full duration of the proposed works, must be obtained with a copy provided to Council.

(Reasons: Statutory requirement and health and safety.)

12. LANDSCAPING - IRRIGATION OF COMMON AND PRIVATE LANDSCAPE AREAS (GC)

All common and private landscape areas including all planters of new multi-unit, commercial, mixed-use and industrial development are to have full coverage by a fully automatic irrigation system. The design, materials and installation are to be in accordance with Sydney Water Codes and satisfy all relevant Australian Standards. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior occupation of the premises.

(Reason: To ensure appropriate landscape maintenance.)

13. LANDSCAPING - TREES PERMITTED TO BE REMOVED (GC)

The following listed trees are permitted to be removed to accommodate the proposed development:

Tree	Height/ Spread (m)	Location
3)Lophostemon confertus	6 x 5	Road reserve
4)Acacia fimbriata	5 x 4	Subject site
5)Jacaranda mimosifolia	8 x 7	Subject site
6)Callistemon viminalis	6 x 7	Subject site
8)Eucalyptus sp.	16 x 9	Subject site
9)Acacia decurrens	5 x 4	Subject site
10) Acacia decurrens	5 x 3	Subject site

All trees permitted to be removed by this consent shall be replaced by species selected from Council's Recommended Tree List.

NOTE: Consent is given for the removal of the existing Tree 3 Lophostemon confertus street tree subject to the following:

- A minimum of one (1) replacement Lophostemon confertus shall be provided within Council's nature strip in Water St
- Trees are to conform to the *NATSPEC guide* and *Guide for assessing the quality of and purchasing of landscape trees* by Ross Clarke, 2003.
- Replacement trees shall be minimum 50 litre container size. Trees are to be true to type, healthy and vigorous at time of delivery and planting, shall be pest and disease

free, free from injury and wounds and self-supporting. Supplied trees are to have an appropriate stem taper. Roots shall generally grow in an outwards (radial) or downwards direction.

- (d) All trees are to be staked and tied with a minimum of three (3) hardwood stakes. Ties are to be hessian and fixed firmly to the stakes, one tie at half the height of the main stem, others as necessary to stabilise the plant.
- (e) Root deflection barriers having a minimum depth of 600mm are to be installed adjacent to all footpaths and driveways.
- (f) Minimum 75mm depth of organic mulch shall be placed within an area 0.5m radius from the base of the tree.

A minimum of 6 x 100 litre size additional trees, which have a minimum mature height of 6 metres shall be planted between the front of the building and the street frontage boundary. Trees are to conform to the *NATSPEC guide* and *Guide for assessing the quality of and purchasing of landscape trees* by Ross Clarke, 2003.

Replacement trees shall be a minimum 50 litre container size. Trees are to conform to the *NATSPEC guide* and *Guide for assessing the quality of and purchasing of landscape trees* by Ross Clarke, 2003. Trees are to be true to type, healthy and vigorous at time of delivery and planting, shall be pest and disease free, free from injury and wounds and self-supporting; and shall be maintained until maturity.

All trees are to be staked and tied with a minimum of three (3) hardwood stakes. Ties are to be hessian and fixed firmly to the stakes, one tie at half the height of the main stem, others as necessary to stabilise the plant.

Root deflection barriers having a minimum depth of 600mm are to be installed adjacent to all footpaths and driveways.

Soil conditioner/fertilizer/moisture retention additive/s are to be applied in accordance with manufacturer's recommendations, and mixed into the backfilling soil after planting tree/s.

A minimum 75mm depth of organic mulch shall be placed within an area 0.5m from the base of the tree.

Details demonstrating compliance shall be demonstrated to the Principal Certifying Authority, prior to the issue of any Occupation Certificate.

(Reason: To ensure appropriate planting back onto the site.)

14. **LANDSCAPING - TREE PRESERVATION (GC)**

All street trees and trees on private property that are protected under Council's controls, shall be retained except where Council's prior written consent has been obtained. The felling, lopping, topping, ringbarking, wilful destruction or removal of any tree/s unless in conformity with this approval or subsequent approval is prohibited.

All healthy trees and shrubs identified for retention on the approved drawings are to be suitably protected in accordance with Australian Standard AS4970 – Protection of Trees on Development prior to the commencement of any works (including any demolition and excavation) and maintained for the duration of the works.

(Reason: To ensure the protection of trees to be retained on the site.)

15. **LIGHTING (GC)**

Any lighting of the premises shall be installed and maintained in accordance with Australian Standard AS 4282-1997: Control of the Obtrusive Effects of Outdoor Lighting so as to avoid annoyance to the occupants of adjoining premises or glare to motorists on nearby roads.

No flashing, moving or intermittent lighting, visible from any public place may be installed on the premises or external signage associated with the development, without the prior approval of Council.

(Reason: To protect the amenity of surrounding development and protect public safety.)

16. MATERIALS – CONSISTENT WITH SUBMITTED SCHEDULE (GC)

All external materials, finishes and colours are to be consistent with the schedule submitted and approved by Council with the development application.

(Reason: To ensure compliance with this consent.)

17. PRINCIPAL CERTIFYING AUTHORITY (PCA) IDENTIFICATION SIGN (GC)

Prior to commencement of any work, signage must be erected in a prominent position on the work site identifying:

- i) the Principal Certifying Authority (PCA) by showing the name, address and telephone number of the PCA;
- ii) the Principal Contractor by showing the Principal Contractor's name, address and telephone number (outside of work hours) for that person; and
- iii) the sign must state that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the work is being carried out, but must be removed when the work has been completed.

This clause does not apply to building work, subdivision work or demolition work that is carried out inside an existing building that does not affect the external walls of the building.

(Reason: Statutory requirement.)

18. PRIVACY - SCREEN PLANTING TO SIDE AND REAR BOUNDARIES (GC)

Evergreen shrubs with a minimum 5 litre container size achieving a minimum mature height of 3m shall be planted along the side and rear boundaries to provide suitable privacy screening. Screen planting shall be maintained at all times. Details of the selected plants shall be submitted to and approved by the Principal Certifying Authority. Compliance with this condition shall be certified by the Principal Certifying Authority, prior to occupation of the premises.

(Reason: To maintain privacy amenity to neighbouring residences.)

19. SITE MANAGEMENT (DURING DEMOLITION AND CONSTRUCTION WORKS)

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standard AS 2601-2001.
- ii) Demolition must be carried out by a registered demolition contractor.

- iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out.
- iv) No blasting is to be carried out at any time during construction of the building.
- v) Care must be taken during demolition/ excavation/ building/ construction to prevent any damage to adjoining buildings.
- vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
- vii) Any demolition and excess construction materials are to be recycled wherever practicable.
- viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
- ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997. All excavated material should be removed from the site in an approved manner and be disposed of lawfully to a tip or other authorised disposal area.
- x) All waste must be contained entirely within the site.
- xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
- xii) All materials on site or being delivered to the site are to generally be contained within the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.
- xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts, etc.) should be kept on site as evidence of approved methods of disposal or recycling.
- xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
- xv) Public footways, include nature strips and roadways adjacent to the site must be maintained and cleared of obstructions during construction. No building materials, waste containers or skips may be stored on the road reserve or footpath without prior separate approval from Council, including payment of relevant fees.
- xvi) Building operations such as brick-cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
- xvii) All site waters during excavation and construction must be contained on site in an approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.
- xviii) Any work must not prohibit or divert any natural overland flow of water.
- xix) Toilet facilities for employees must be provided in accordance with WorkCover NSW.
- xx) Protection pads are to be installed to the kerb and gutter where trucks and vehicles enter the site.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

20. **STORMWATER MANAGEMENT PLAN - CERTIFICATION REQUIREMENT (GC)**

A detailed Stormwater Management Plan (SWMP) in line with Council's Stormwater Management Code is to be prepared and certified by a practicing Chartered Professional Engineer on the National Professional Engineer's Register (NPER) at Engineers Australia

and submitted to the Principal Certifying Authority and Council, prior to the issue of a Construction Certificate. The SWMP is to be based on the approved development as modified by any conditions of consent.

(Reason: To ensure appropriate provision is made for the disposal and management of stormwater generated by the development, and to ensure public infrastructure in Council's care and control is not overloaded.)

21. SYDNEY WATER - STAMPED PLANS PRIOR TO COMMENCEMENT (GC)

The approved plans must be submitted to a Sydney Water Quick Check agent or Customer Centre to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Plans will be appropriately stamped.

For Quick Check agent details please refer to the web site www.sydneywater.com.au (see Building Developing and Plumbing then Quick Check) or telephone 13 20 92. The consent authority or a Certifying Authority must ensure that a Quick Check agent/Sydney Water has stamped the plans before the commencement of work.

(Reason: Compliance with Sydney Water requirements.)

22. UTILITIES AND SERVICES - PROTECTION OF (GC)

Any footings or excavation to be located or undertaken adjacent to Council's stormwater must be designed to address the following requirements:

- i) all footings and excavation must be located wholly within the site and clear of any easement boundaries;
- ii) all footings and excavation must be located a minimum of 1000mm from the centreline of the pipeline or 500mm from the outside of the pipeline, whichever is the greater distance from the centreline; and
- iii) footings must extend to at least the depth of the invert of the pipeline unless the footings are to be placed on competent bedrock.

If permanent excavation is proposed beneath the obvert of the pipeline, suitable means to protect the excavation and proposed retaining structures from seepage or other water flow from the pipeline and surrounding subsoil, must be provided. The design must be prepared by a qualified practicing Structural/Civil Engineer.

Construction plans must be approved by the appropriate utility's office (e.g. council, Sydney Water Corporation) to demonstrate that the development complies with the utility's requirements.

The applicant must provide written evidence (e.g. compliance certificate, formal advice) of compliance with the requirements of all relevant utility providers (e.g. Water, Energy, Telecommunications, Gas).

(Reason: To ensure protection of Council assets.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A CONSTRUCTION CERTIFICATE (CC)

23. ACCESS - ACCESS FOR PEOPLE WITH DISABILITIES (CC)

Access for people with disabilities must be provided in accordance with the requirements of

the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

24. **ACCESS - DISABLED TOILETS (CC)**

Plans and details of the disabled toilet/s complying with the relevant Australian Standards, the Building Code of Australia, and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

25. **ACID SULFATE SOILS - CERTIFICATION OF SOIL REMOVED FROM THE SITE (CC)**

A Certificate is to be provided by a suitably qualified geo-technical engineer stating that no more than 1 tonne of soil will be removed from the site and the groundwater table will not be affected by the development. This Statement shall be submitted to Council, prior to the issue of a Construction Certificate.

(Reason: Compliance and environmental protection.)

26. **ARBORIST REPORT – INITIAL (CC)**

The applicant must engage a suitably qualified and experienced arborist (Australian Qualification Framework Level 5 or above) to assess the impact of the proposed works and determine best practices (e.g. minimise compaction, soil build up and or excavation within the Primary Root Zone*) to ensure the longevity of the trees to be retained. The arborist is to prepare and submit, to the satisfaction of the Principal Certifying Authority, a report prior to the issue of a Construction Certificate, documenting the measures to be employed and certifying that they have been implemented.

- i) *Primary root zone = 10 x trunk diameter 1400mm from ground level (measured as a radius from the centre of the trunk).

(Reason: Qualified assessment of impact of proposed works on trees to be retained on the site.)

27. **BASIX COMMITMENTS (CC)**

The approved BASIX Certificate shall be submitted to the Principal Certifying Authority with the application for a Construction Certificate.

Where a change or changes are proposed in the BASIX commitments, the applicant must submit a new BASIX Certificate to the Principal Certifying Authority and Council. If any proposed change in the BASIX commitments is inconsistent with the development consent the applicant will be required to submit a modification to the development consent to Council under Section 96 of the Environmental Planning and Assessment Act 1979.

All commitments in the BASIX Certificate must be shown on the plans accompanying the Construction Certificate.

(Reason: Statutory compliance.)

28. BICYCLE STORAGE PROVISION (CC)

On-site provision for bicycle storage facilities shall be in accordance with the Strathfield Consolidated Development Control Plan 2005. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Compliance with SDCDP 2005 and to encourage sustainable transport options.)

29. BUILDING CODE OF AUSTRALIA - COMPLIANCE WITH (CC)

All architectural drawings, specifications and related documentation shall comply with the Building Code of Australia (BCA). All work must be carried out in accordance with the requirements of the Building Code of Australia (BCA).

In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of that Act, such a contract of insurance is to be in force before any building work authorised to be carried out by the consent commences.

Details demonstrating compliance with this condition are to be submitted to the Principle Certifying Authority, prior to issue of the Construction Certificate.

(Reason: This is a 'prescribed' condition under clause 98(1) of the Environmental Planning and Assessment Regulation 2000.)

30. CAR PARKING - BASEMENT CAR PARKING REQUIREMENTS (CC)

Details demonstrating compliance with the following is to be submitted to the Principal Certifying Authority, prior to issue of the Construction Certificate:

- i) Minimal internal clearance of the basement is 2.2m in accordance with BCA requirements.
- ii) Driveways shall comply with Australian/New Zealand Standard AS/NZS 2890.1:2004 - Parking facilities - Off-street car parking and achieve a maximum gradient of 1:4.
- iii) Basement entries and ramps/driveways within the property are to be no more than 3.5m wide.
- iv) Provision of pump-out systems and stormwater prevention shall be in accordance with Council's Stormwater Management Guide.

(Reason: To ensure suitable development.)

31. CAR PARKING - DISABLED CAR PARKING SPACES (CC)

car parking spaces shall be provided as part of the total requirement shall for disabled

persons. These spaces shall be a minimum of 2.4m wide x 5.4m long and located near pedestrian access routes designed for disabled persons. Each space shall be clearly marked as such. A shared area 2.4 m wide x 5.4m long shared area should be provided. Bollard shall be placed in this shared area.

Car parking for people with disabilities shall be provided in accordance with the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Prior to the issue of a Construction Certificate, the plans shall be notated to demonstrate compliance.

The above details shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate.

(Reason: To ensure adequate parking for persons with a disability.)

32. CAR PARKING - REQUIREMENTS FOR MULTIPLE USE BUILDINGS (CC)

The following car parking and service vehicle requirements apply:-

- i) A minimum **(72) car spaces** shall be provided on the development site. This shall consist of:
 - (52) residential spaces;
 - (13) visitor spaces;
 - (7) commercial spaces;
 - 10% car parking spaces for people with mobility impairment, in accordance with AS 2890.1.
- ii) All car spaces shall be allocated and marked according to this requirement.
- iii) If the development is to be strata subdivided, the car park layout must reflect the above allocation and thereafter be regarded as part of the entitlement of that strata lot.
- iv) Under no circumstances shall parking spaces be sold, let or otherwise disposed of for use other than in accordance with this condition.
- v) Each car parking space shall have minimum dimensions in accordance with the relevant Australian Standard and be provided on-site in accordance with the approved plans.
- vi) The parking bays shall be delineated by line marking.
- vii) Visitor spaces shall be clearly line marked and/or signposted and shall only be used by persons visiting residents of the property or commercial/business/retail premises located within the development. Visitor spaces shall not be allocated as permanent residential parking spaces. Access to visitor parking spaces shall not be restricted without development approval and a sign shall be erected at the vehicular entrance indicating the availability of visitor parking.
- viii) The following traffic control measures shall be implemented on site:-
 - Signage indicating 'Entry Only' shall be prominently displayed at the entrance to the development.
 - Signage indicating 'Exit Only' shall be prominently displayed at the exit to the development.
 - One-Way directional arrows shall be painted on the driveway pavement to indicate the required vehicular directional movement through the car parking area.

Details demonstrating compliance with this condition shall be submitted to and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To ensure car parking provision in accordance with this consent.)

33. CAR PARKING – STACKED (CC)

Any stacked parking spaces (maximum 2 spaces, nose to tail) must be attached to the same strata title comprising a single dwelling unit or commercial/retail tenancy, subject to the maximum parking limit applying. The stacked parking spaces must be designated (with appropriate signage) for employee or tenant parking only (not visitor parking). Details in this regard must be reflected in the plan documentation to be lodged with a Construction Certificate application. Manoeuvring of stacked vehicles must occur wholly within the property.

(Reason: Compliance and appropriate allocation of parking.)

34. CAR PARKING - VEHICULAR ACCESS RAMPS (CC)

Vehicular access ramps shall comply with the provisions of AS/NZS 2890.1:2004. Plans to be submitted shall contain the following details:

- i) Longitudinal section along the extreme wheel paths of each driveway/access ramp at a scale of 1:25 demonstrating compliance with the scraping provisions of AS/NZS 2890.1:2004. It shall include all levels and grades, including those levels stipulated as boundary levels, both existing and proposed. It shall extend from the centre-line of the roadway through to the parking area.
- ii) Sections showing the clearance to the underside of any overhead structure (minimum headroom requirements 2200mm minimum for standard headroom clearance or 2400mm where disabled access provisions are to be provided) demonstrating compliance with the provisions of AS/NZS 2890.1:2004.
- iii) Longitudinal section along the gutter line showing how it is intended to transition the vehicular crossing into the existing kerb and gutter. Boundary levels shall generally run parallel with the kerb levels.
- iv) Location of verge trees, street furniture and service installations.
- v) Superimposition of vehicle turning circles for access into parking spaces.
- vi) Certification that the design complies with AS/NZS 2890.1:2004 by a Qualified Engineer.

The certification referred to in (vi) above shall be submitted to the Principal Certifying Authority prior to the issue of a Construction Certificate (for the design) and to the Principal Certifying Authority prior to the issue of any Occupation Certificate for the 'as-built works'.

(Reason: To ensure adequate vehicular access can be achieved.)

35. CAR PARKING - COMPLIANCE WITH AS/NZS 2890.1:2004 (CC)

Car parking dimensions must comply with the Australian/New Zealand Standard AS/NZS 2890.1:2004 - Parking facilities - Off-street car parking. Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To ensure compliance with Australian Standards relating to parking of vehicles.)

36. CAR PARKING - VEHICULAR CIRCULATION, AISLE AND RAMP WIDTHS (CC)

The aisle widths, internal circulation, ramp widths and grades of the car park shall comply with the Roads and Traffic Authority Guidelines and AS/NZS 2890.1:2004 - Off-Street Car Parking Code.

Vehicular manoeuvring paths are to be prepared demonstrating that all vehicles can enter or depart the site in a forward direction without encroaching on required car parking spaces.

(Reason: To ensure compliance with Australian Standards relating to manoeuvring, access and parking of vehicles.)

37. CAR PARKING - VEHICULAR CROSSING WIDTH AT PROPERTY BOUNDARY (CC)

Vehicular crossings are to have a maximum width of 3m at the property boundary. Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Compliance with SCDPC 2005.)

38. COMMENCEMENT OF WORKS (NO WORKS UNTIL A CC IS OBTAINED)

Building work, demolition or excavation must not be carried out until a Construction Certificate has been issued by either Strathfield Council or a Principal Certifying Authority.

Demolition of any part of a building triggers 'commencement of erection of building' pursuant of section 81A(2) of the EP&A Act 1979. Accordingly, demolition works must not commence until a Construction Certificate has been issued, a Principal Certifying Authority has been appointed and a Notice of Commencement has been issued.

(Reason: To ensure compliance with statutory provisions.)

39. CONSTRUCTION AND ENVIRONMENTAL MANAGEMENT PLAN (CC)

The applicant must prepare and submit a Construction and Environmental Management Plan (CEMP) to the Principal Certifying Authority, including:

- i) Detailed information on any approvals required from other authorities prior to or during construction.
- ii) Traffic management, including details of:
 - ingress and egress of vehicles to the site;
 - management of loading and unloading of materials;
 - the location of heavy vehicle parking off-site; and
 - designated routes for vehicles to the site.
- iii) The proposed areas within the site to be used for a builder's site office and amenities, the storage of excavated material, construction materials and waste containers during the construction period.
- iv) Erosion and sediment control, detailing measures and procedures consistent with the requirements of Council's guidelines for managing stormwater, including:
 - the collection and treatment of stormwater and wastewater generated on site prior to discharge; and
 - procedures to prevent run-off of solid material and waste from the site.
- v) Waste management, including:
 - details of the types and estimated volumes of waste materials that will be generated;
 - procedures for maximising reuse and recycling of construction materials; and
 - details of the off-site disposal or recycling facilities for construction waste.
- vi) Dust control, outlining measures to minimise the generation and off-site transmission of dust and fine particles, such as watering or damp cloth fences.
- vii) A soil and water management plan, which includes:
 - measures to minimise the area of soils exposed at any one time and conserve top soil;
 - identification and protection of proposed stockpile locations;

- preservation of existing vegetation and revegetation;
 - measures to prevent soil, sand, sediments leaving the site in an uncontrolled manner;
 - measures to control surface water flows through the site in a manner that diverts clean run-off around disturbed areas, minimises slope gradient and flow distance within disturbed areas, ensures surface run-off occurs at non-erodible velocities, and ensures disturbed areas are promptly rehabilitated;
 - details of sediment and erosion control measures in place before work commences;
 - measures to ensure materials are not tracked onto the road by vehicles entering or leaving the site; and
 - details of drainage to protect and drain the site during works.
- viii) Asbestos management procedures:
- Anyone who removes, repairs or disturbs bonded or a friable asbestos material must hold a current removal licence from Workcover NSW holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal License which ever applies and a current WorkCover Demolition License where works involve demolition. To find a licensed asbestos removalist please see www.workcover.nsw.gov.au
 - Removal of asbestos by a person who does not hold a Class A or Class B asbestos removal license is permitted if the asbestos being removed is 10m² or less of non-friable asbestos (approximately the size of a small bathroom). Friable asbestos materials must only be removed by a person who holds a current Class A asbestos license.
 - Before starting work, a work site-specific permit approving each asbestos project must be obtained from Workcover NSW. A permit will not be granted without a current Workcover licence. All removal, repair or disturbance of or to asbestos material must comply with the following:
 - The Work Health and Safety Act 2011;
 - The Work Health and Safety Regulation 2011;
 - How to Safety Remove Asbestos Code of Practice – WorkCover 2011; and
 - Safe Work Australia Code of Practice for the Management and Control of Asbestos in the Workplace.
 - Following completion of asbestos removal works undertaken by a licensed asbestos removalist re-occupation of a workplace must not occur until an independent and suitably licensed asbestos removalist undertakes a clearance inspection and issues a clearance certificate.
 - The developer or demolition contractor must notify adjoining residents at least two (2) working days (i.e. Monday to Friday exclusive of public holidays) prior to the commencement of asbestos removal works. Notification is to include, at a minimum:
 - the date and time when asbestos removal works will commence;
 - the name, address and business hours contact telephone number of the demolisher, contractor and/or developer;
 - the full name and license number of the asbestos removalist/s; and
 - the telephone number of WorkCover's Hotline 13 10 50
 - warning signs informing all people nearby that asbestos removal work is taking place in the area. Signs should be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs should be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs should be in accordance with AS 1319-1994 Safety signs for the occupational environment for size, illumination, location and maintenance; and
 - appropriate barricades installed as appropriate to prevent public access

and prevent the escape of asbestos fibres. Barricades must be installed prior to the commencement of asbestos removal works and remain in place until works are completed.

(Reason: Safety, amenity and protection of public infrastructure and the environment.)

40. **COUNCIL PERMITS – FOR ALL ACTIVITIES ON COUNCIL LAND (CC)**

Works Permit

(as per Section 68 of the Local Government Act 1993 and Section 138 and 139 of the Roads Act 1993)

A Works Permit is required for construction of a vehicular crossing (driveway), new stormwater down pipe connection to kerb and gutter, new footpath and/or stormwater connection. A Works Permit Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Standing Plant Permit

This permit must be applied for where it is intended to park a concrete pump, crane or other plant on the roadway or footpath. A Standing Plant Permit Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Skip Bin Permit

This permit must be applied for if you intend to place a skip bin on the roadway or footpath. A Skip Bin Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Temporary Full or Part Road Closure Permit

This permit must be applied for if you require a full or a part road closure to take place to assist in your construction works. Please use the Works Permit Application Form, which is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Hoarding Permit

This permit must be applied for if you intend to erect a Class A (fence type) or Class B (overhead type) hoarding along the street frontage(s). A Hoarding Permit Application Form is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Work Zone Permit

This permit must be applied for if you require permanent parking along the kerbside at the front of the site during construction works. A Work Zone Permit Application Form is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Ground Anchoring Permit

This permit must be applied for, for the installation of ground anchors under Council's footway/road reserve. It does not cover ground anchors under private properties. A separate approval is required to be obtained from Roads and Maritime Services (RMS) if it is proposed to install ground anchors under a State or Classified Regional Road (please refer to the end of this application form for more information).

(Reason: Council requirement)

41. DILAPIDATION REPORT - PRE-COMMENCEMENT (CC)

Subject to access being granted, a pre-commencement Dilapidation Report is to be undertaken on all adjoining properties, which in the opinion of a suitably qualified engineer, could be potentially affected by the construction of the project. The Dilapidation Report shall be carried out prior to the issue of a Construction Certificate.

The Dilapidation Report is to be prepared by a suitably Qualified Engineer with current Corporate Membership with the Institution of Engineers, Australia or Geotechnical Practitioner. The report shall include a photographic survey of adjoining properties detailing the physical condition of those properties, both internally and externally, including walls, ceilings, roof, structural members and other such items.

If access for undertaking the dilapidation survey is denied by an adjoining owner, the applicant must demonstrate, in writing, to Council's satisfaction attempts have been made to obtain access and/or advise the affected property owner of the reason for the survey and these attempts have been unsuccessful. Written concurrence must be obtained from Council in such circumstances.

The Report shall cover structural and geotechnical factors likely to arise from the development. A copy of this Report shall be submitted to Council as a record. The person having the benefit of the development consent must, at their own cost, rectify any damage caused to other properties during the construction of the project.

(Reason: To ensure no damage to adjoining properties occurs.)

42. DRIVEWAY WIDTH - MULTI-UNIT DEVELOPMENT (CC)

The internal driveway must be a minimum 5.50m wide (clear width) for the first 6 metres inside the property so as to allow entering & exiting vehicles to pass within the site. Should the driveway narrow after this point it is then to be designed with a minimum 1.5m x 1.5m splay to allow the passing to work. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior the issue of a Construction Certificate.

(Reason: Safety and traffic management.)

43. DRIVEWAY DESIGN - SPEED HUMP AND STOP SIGN ON EXIT (CC)

The applicant shall install a stop sign and a speed hump at the exit from the site. The stop sign must be accompanied by the associated line marking and the speed hump shall be set back by 1.5 metres from the boundary alignment. The devices shall be designed and constructed in accordance with the provision of all relevant Australian Standards. The building plans shall indicate compliance with this requirement, prior to the issue of a Construction Certificate.

(Reason: Traffic safety and management.)

44. EXCAVATION - AFFECTING ADJOINING LAND (CC)

If an excavation associated with the approved development extends below the level of the base of the footings of a building on an adjoining allotment of land, the person having the benefit of the development consent must, at the person's own expense, comply with the requirements of clause 98E of the Environmental Planning and Assessment Regulation

2000, including:

- i) protect and support the adjoining premises from possible damage from the excavation, and
- ii) where necessary, underpin the adjoining premises to prevent any such damage.

The condition referred to in subclause (i) does not apply if the person having the benefit of the development consent owns the adjoining land or the owner of the adjoining land has given consent in writing to that condition not applying. Details shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Structural safety.)

45. FEES - PUBLIC RISK INSURANCE POLICY (CC)

A Public Risk Insurance Policy with a minimum cover of \$20 million in relation to the occupation of and works within Council's road reserve, for the full duration of the proposed works, must be obtained with a copy also provided to Council.

The Policy is to note Council as an interested party. The copy is to be provided to Council, prior to the issue of a Construction Certificate.

(Reason: Ensure public risk is mitigated.)

46. HAZARDOUS GOODS AND WASTE (CC)

Dangerous and hazardous goods shall be stored in accordance with NSW WorkCover requirements and AS1940-2004 - The Storage and Handling of Flammable and Combustible Liquids.

Hazardous waste must be contained, managed and disposed of in a responsible manner in accordance with the Protection of Environment and Operations Act 1997, NSW Environment Protection Authority (EPA) and the New South Wales WorkCover Authority.

Material Safety Data Sheets of all hazardous substances used, such as bleaches and nail products must be kept on site and readily available to all staff. Staff must be trained how to safely use and store these chemicals prior to the commencement of work.

Details demonstrating compliance with the requirements of this condition are to be submitted to the satisfaction of the Principal Certifying Authority prior to the issue of any Construction Certificate.

(Reason: Health and safety.)

47. LANDSCAPING - MAINTENANCE STRATEGY (CC)

To ensure the survival of landscaping following works, a landscape maintenance strategy for the owner/occupier to administer over a 12 month establishment period following the issue of the Occupation Certificate shall be prepared and provided to the satisfaction of the Principal Certifying Authority with the Construction Certificate application. The strategy is to address maintenance issues such as, but not limited to plant survival, irrigation, soil testing, weeding, staking, fertilizing, remedial pruning and plant replacement.

(Reason: Ensure landscape survival.)

48. **PRIVACY - OBSCURE GLAZING IN WET AREAS (CC)**

All bathroom, ensuite and toilet windows shall be installed with obscure glazing. Plans shall be notated accordingly and details demonstrating compliance submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Privacy amenity.)

49. **SECTION 94 CONTRIBUTION PAYMENT - DIRECT CONTRIBUTIONS PLAN (CC)**

In accordance with the provisions of Section 94(1)(b) of the Environmental Planning and Assessment Act 1979 and the Strathfield Direct Development Contributions Plan 2010-2030, a contribution in the form of cash, cheque or credit card (financial transaction fee applies) shall be paid to Council for the following purposes:

Provision of Community Facilities	\$120,399.13
Provision of Major Open Space	\$549,555.69
Provision of Local Open Space	\$120,933.97
Provision Roads and Traffic Management Administration	\$22,488.96
	\$10,417.24
TOTAL	\$823,794.99

The total amount of the contribution is valid as at the date of determination and is subject to quarterly indexation. Contributions shall be indexed at the time of payment in accordance with clause 2.14 of the Strathfield Direct Development Contributions Plan 2010-2030.

Contributions must be receipted by Council and submitted to the Accredited Certifier, prior to the issue of any Construction Certificate.

Please present a copy of this condition when paying the contribution at the Customer Service Centre so that it can be recalculated.

Note: A copy of Strathfield Council's Section 94 Direct Development Contributions Plan may be downloaded from Council's website.

(Reason: To enable the provision of public amenities and services required/anticipated as a consequence of increased demand resulting from the development.)

50. **SECURITY PAYMENT - DAMAGE DEPOSIT FOR COUNCIL INFRASTRUCTURE (CC)**

A security (damage deposit) of **\$33,000.00** (calculated in accordance with Council's adopted Fees and Charges) shall be paid to Council, prior to the issue of a Construction Certificate.

The deposit is required as security against any damage to Council property during works on the site. The applicant must bear the cost of all restoration works to Council's property damaged during the course of this development. All building work must be carried out in accordance with the Building Code of Australia.

Payment may be accepted in the form of cash, bank guarantee, cheque or credit card (financial transactions fees apply). Note: Additional fees apply for the lodgement of a bank guarantee in lieu of cash bond applies in accordance with Council's adopted Fees and Charges.

Any costs associated with works necessary to be carried out to rectify any damages caused

by the development, shall be deducted from the Damage Deposit.

Note: Should Council property adjoining the site be defective e.g. cracked footpath, broken kerb etc., this should be reported in writing, or by photographic record, submitted to Council at least seven (7) days prior to the commencement of any work on site. This documentation will be used to resolve any dispute over damage to infrastructure. It is in the applicant's interest for it to be as full and detailed as possible.

The damage deposit shall be refunded upon completion of all works upon receipt of a Final Occupation Certificate stage and inspection by Council.

(Reason: Protection of Council infrastructure.)

51. **TRAFFIC - CONSTRUCTION TRAFFIC MANAGEMENT PLAN (CC)**

A Construction Traffic Management Plan (CTMP) is to be prepared by an appropriately qualified Traffic Management Consultant and submitted to and approved by Council's Engineering Section, prior to the commencement of any works including demolition.

The following matters should be addressed in the CTMP (where applicable):

- i) description of the demolition, excavation and construction works;
- ii) site plan/s showing the site, roads, footpaths, site access points and vehicular movements;
- iii) size, type and estimated number of vehicular movements (including removal of excavated materials, delivery of materials and concrete to the site);
- iv) proposed route(s) from the arterial (state) road network to the site and the proposed route from the site back to the arterial road network;
- v) impacts of the work and vehicular movements on the road network, traffic and pedestrians and proposed methods to safely manage pedestrians and construction related vehicles in the frontage roadways;
- vi) any Traffic Control Plans (TCP's) proposed to regulate traffic and pedestrian movements for construction activities (such as concrete pours, crane installation/removal etc.);
- vii) proposed hours of construction related activities and vehicular movements to and from the site;
- viii) current/proposed approvals from other Agencies and Authorities (including Roads and Maritime Services, Police and State Transit Authority);
- ix) any activities proposed to be located or impact upon Council's road, footways or any public place;
- x) measures to maintain public safety and convenience;
- xi) any proposed road and/or footpath closures;
- xii) turning areas within the site for construction and spoil removal vehicles, allowing a forward egress for all construction vehicles on the site;
- xiii) locations of work zones (where it is not possible for loading/unloading to occur on the site) in the frontage roadways accompanied by supporting documentation that such work zones have been approved by the Local Traffic Committee and Council;
- xiv) location of any proposed crane and concrete pump and truck standing areas on and off the site (and relevant approvals from Council for plant on road);
- xv) a dedicated unloading and loading point within the site for all construction vehicles, plant and deliveries;
- xvi) material, plant and spoil bin storage areas within the site, where all materials are to be dropped off and collected;
- xvii) on-site parking area for employees, tradespersons and construction vehicles as far as possible;
- xviii) proposed areas within the site to be used for the storage of excavated material,

- construction materials and waste and recycling containers during the construction period; and
- xix) how it is proposed to ensure that soil/excavated material is not transported onto surrounding footpaths and roadways.

(Reason: To mitigate traffic impacts on the surrounding area during the construction period.)

52. VEHICULAR CROSSINGS - WORKS PERMIT FOR CONSTRUCTION OF (CC)

Full-width, heavy-duty concrete vehicular crossing(s) shall be provided across the footpath at the entrance(s) and/or exit(s) to the site and designed in accordance with Council's guidelines and specifications. In this regard, a Works Permit is to be obtained (available from Council's Customer Services Centre or downloaded from Council's website), and the appropriate fees and charges paid, prior to the lodgement of a Construction Certificate.

(Reason: To ensure appropriate access to the site can be achieved.)

53. VENTILATION SYSTEMS – MECHANICAL (CC)

The mechanical ventilation system is to comply with the following:

- i) The Building Code of Australia;
- ii) Protection of the Environment Operations Act 1997; and
- iii) Australian Standard AS1668-1991.

In addition, odour control measures, such as activated carbon or catalytic oxidisers, must be used to treat ventilation gases prior to discharge. The method of odour control must be designed by a suitably qualified mechanical ventilation engineer.

Details demonstrating compliance with the above are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To ensure the mechanical ventilation system complies with the relevant requirements/standards.)

54. WASTE MANAGEMENT PLAN (CC)

A Waste Management Plan (WMP) is to be provided in accordance with Part H of Strathfield Consolidated Development Control Plan 2005. All requirements of the approved Waste Management Plan must be implemented during demolition, construction and on-going use of the premises.

The WMP must identify the types of waste that will be generated and all proposals to re-use, recycle or dispose of the waste. The WMP is to be submitted to the Principal Certifying Authority, prior to issue of the Construction Certificate.

NOTE: The property must be inspected by a Council Waste Officer prior to the issue of an Occupation Certificate so as to ensure that the correct number of general waste and recycling bins are ordered from Strathfield Council.

(Reason: To ensure appropriate management of waste.)

55. WASTE - SEPARATE WASTE AREAS FOR MIXED-USE DEVELOPMENTS (CC)

The building must include not less than two independently designated areas or garbage

rooms for commercial and for residential occupants; to keep commercial waste and recycling separate to residential waste and recycling.

(Reason: To ensure the appropriate separation and collection of waste generated by commercial and residential activities.)

56. WASTE - GARBAGE ROOMS OR GREASE ARRESTOR ROOMS (CC)

Garbage rooms or grease arrester rooms must be constructed of solid material: cement rendered and steel trowelled to a smooth even surface. The door to the garbage room is to be designed and constructed to ensure the room is vermin proof and can be opened from the inside at all times. The garbage room is to be ventilated to the external air by natural ventilation or an approved air handling exhaust system.

(Reason: To keep garbage rooms in a clean and sanitary condition to protect public health.)

57. WATER SUSTAINABILITY - WATER SENSITIVE URBAN DESIGN (CC)

Details of the Water Sensitive Urban Design (WSUD) components (stormwater treatment measures) shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate. Details shall demonstrate compliance with the water conservation and stormwater quality targets set out under Sections 3.1 and 3.2 respectively under Part N of the SCDCP 2005, and be prepared by a suitably qualified professional engineer.

(Reason: To promote Water Sensitive Urban Design.)

58. WORKS WITHIN THE ROAD RESERVE (CC)

Detailed drawings including long and short sections and specifications of all works within existing roads (including but not limited to structures, road works, driveway crossings, footpaths and stormwater drainage) shall be submitted to and approved by Council under Section 138 of the Roads Act 1993 and all fees and charges paid, prior to the issue of a Construction Certificate.

Detailed drawings and specifications are to be prepared and certified by an appropriately qualified Civil Engineer.

Upon completion of the works, the Applicant is to provide to Council with electronic copies of 'Work as Executed Plans'. The plans are to show relevant dimensions and finished levels and are to be certified by a surveyor.

The Applicant is to provide to Council, in an approved format, details of all public infrastructure created as part of the works.

All civil engineering works adjacent/near/outside Water Street and Punchbowl Road are to be fully supervised by Council. A maintenance period of six (6) months shall apply to the work, after it has been completed and approved. In that period the Applicant shall be liable for any part of the work which fails to perform in the manner outlined in Council's specifications, or as would reasonably be expected under the design conditions.

(Reason: To ensure compliance of engineering works/Council assets are constructed to acceptable standards for engineering works.)

59. WORKS ZONE - APPROVAL BY COUNCIL'S TRAFFIC COMMITTEE (CC)

An application for a 'Works Zone' must be submitted to and approved by the Strathfield Council Traffic Committee prior to the commencement of any site work (including demolition).

The suitability of the proposed length and duration of the Works Zone is to be demonstrated in the application for the Works Zone. The application for the Works Zone must be submitted to Council at least six (6) weeks prior to the commencement of work on the site to allow for assessment and tabling of agenda for the Strathfield Council Traffic Committee.

The requirement for a Works Zone may be varied or waived only if it can be demonstrated in the Construction Traffic Management Plan (to the satisfaction of Council) that all construction related activities (including all loading and unloading operations) can and will be undertaken wholly within the site. The written approval of Council must be obtained to provide a Works Zone or to waive the requirement to provide a Works Zone prior to the commencement of any site work.

(Reason: Council requirement.)

CONDITIONS TO BE SATISFIED PRIOR TO THE COMMENCEMENT OF WORKS (CW)

60. APPOINTMENT OF A PRINCIPAL CERTIFYING AUTHORITY (PCA) (CW)

No work shall commence in connection with this Development Consent until:

- i) A construction certificate for the building work has been issued by the consent authority or a Principal Certifying Authority.
- ii) The person having the benefit of the development consent has appointed a principal certifying authority for the building work, and notified the principal certifying authority that the person will carry out the building work as an owner/builder, if that is the case.
- iii) The principal certifying authority has, no later than 2 days before the building work commences:
 - notified the Council of his or her appointment, and
 - notified the person having the benefit of the development consent of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- iv) The person having the benefit of the development consent, if not carrying out the work as an owner-builder, has:
 - appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved;
 - notified the principal certifying authority of such appointment; and
 - unless that person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- v) The person having the benefit of the development consent has given at least 2 days notice to the Council of the person's intention to commence the erection of the building.

Note: If the principal certifying authority is the Council, the nomination will be subject to the payment of a fee for the service to cover the cost of undertaking all necessary inspections and the issue of the appropriate certificates.

Under the Environment Planning and Assessment (Quality of Construction) Act, 2003, a sign must be erected in a prominent position on the work site showing the name, address and telephone number of the principal certifying authority; the name of the principal contractor (if any) for the building work and a telephone number at which that person may

be contacted outside working hours. That sign must also state that unauthorised entry is prohibited. The sign must not be removed until all work has been completed.

(Reason: Statutory requirement.)

61. NOTICE OF COMMENCEMENT (CW)

No work shall commence until the following details are submitted to Council:

- i) a Notice of Commencement (form will be attached with issue of a Construction Certificate or available from our website) within two (2) days of the date on which it is proposed to commence works associated with the Development Consent;
- ii) details of the appointment of a Principal Certifying Authority (either Council or another Principal Certifying Authority); and
- iii) details of the name, address and licence details of the Builder.

(Reason: Statutory requirement.)

CONDITIONS TO BE SATISFIED DURING DEMOLITION AND BUILDING WORKS (DW)

62. CONTAMINATED LAND UNEXPECTED FINDS (DW)

In the instance works cause the generation of odours or uncovering of unexpected contaminants works are to immediately cease, Council is to be notified and a suitably qualified environmental scientist appointed to further assess the site.

The contaminated land situation is to be evaluated by the supervising environmental consultant and an appropriate response determined in consultation with the applicant, which is agreed to by Strathfield Council's Environmental Services Manager.

Note: Council may also request that a NSW EPA accredited site auditor is involved to assist with the assessment of the contaminated land situation and review any new contamination information. The applicant must also adhere to any additional conditions which may be imposed by the accredited site auditor.

(Reason: To ensure compliance with statutory requirements.)

63. FILL MATERIAL (DW)

The only waste derived material which may be received at the development site is:

- i) Virgin excavated material (within the meaning of the Protection of the Environment Operations Act 1997), and
- ii) any other waste-derived material the subject of a resource recovery exemption under cl.51A of the Protection of the Environment Operations (Waste) Regulation 2005 that is permitted to be used as fill material.

Any (b)-type material received at the development site must be accompanied by documentation certifying by an appropriately qualified environmental consultant the materials compliance with the exemption conditions; and this documentation must be provided to the Principal Certifying Authority on request.

(Reason: To ensure imported fill is of an acceptable standard for environmental protection purposes.)

64. OBSTRUCTION OF PUBLIC WAY NOT PERMITTED DURING WORKS (DW)

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances, without the prior approval of Council.

(Reason: To maintain public access and safety.)

65. PUBLIC INFRASTRUCTURE AND SERVICES (DW)

The applicant must comply with the requirements (including financial costs) of any relevant utility provider (e.g. Energy Australia, Sydney Water, Telstra, RMS, Council etc.) in relation to any connections, works, repairs, relocation, replacements and/or adjustments to public infrastructure or services affected by the development.

(Reason: To maintain public infrastructure and/or services.)

66. SITE REQUIREMENTS DURING DEMOLITION AND CONSTRUCTION

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standards AS 2601-2001.
- ii) Demolition must be carried out by a registered demolition contractor.
- iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out with close boarded, hardwood timber footpath protection pads. The pad shall cover the entire width of the footpath opening for the full width of the fence.
- iv) No blasting is to be carried out at any time during construction of the building.
- v) Care must be taken during demolition/ excavation/ building/ construction to prevent any damage to adjoining buildings.
- vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
- vii) Any demolition and excess construction materials are to be recycled wherever practicable.
- viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
- ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997.
- x) All excavated material should be removed from the site in the approved manner and be disposed of lawfully to a tip or other authorised disposal area.
- xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
- xii) All materials on site or being delivered to the site are to generally be contained within the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.
- xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts etc.) should be kept on site as evidence of approved methods of disposal and recycling.
- xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
- xv) Public footways and roadways adjacent to the site must be fully maintained and

cleared of obstructions during construction unless prior separate approval from Council is obtained including payment of relevant fees.

- xvi) Building operations such as brick cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
- xvii) All site waters during excavation and construction must be contained on site in an approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.
- xviii) Stamped plans, specifications, documentation and the consent shall be available on site at all times during construction.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

67. SURVEY REPORT OF APPROVED LEVELS DURING AND POST CONSTRUCTION (DW)

A Survey Certificate to Australian Height Datum shall be prepared by a Registered Surveyor as follows:

- i) At the completion of the first structural floor level prior to the pouring of concrete indicating the level of that floor and the relationship of the building to the boundaries.
- ii) At the completed height of the building, prior to the placement of concrete inform work, or the laying of roofing materials.
- iii) At the completion of the development.

Progress certificates in response to points (1) through to (3) shall be provided to the Principal Certifying Authority at the time of carrying out relevant progress inspections. Under no circumstances is work allowed to proceed until such survey information is submitted to and approved by the Principal Certifying Authority.

(Reason: To ensure compliance with the approved plans.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE (OC)

68. CAR PARKING - SURPLUS VEHICULAR CROSSINGS (OC)

All surplus vehicular crossings and/or kerb laybacks must be removed and reinstated with concrete kerb and gutter or to the existing edging profile as specified by Council. The nature strip is to be restored and the footpath area reinstated. All of the above are to be restored to the satisfaction of Council's Engineer and at full cost to the applicant, prior to the issue of any Occupation Certificate.

(Reason: Maintenance of public infrastructure.)

69. CAR PARKING - VISITOR CAR PARKING SIGNAGE (OC)

A sign shall be erected in a suitable location on the property near the driveway entrance indicating where visitor parking is available on the site. Signage shall also be erected above the visitor parking itself. Details demonstrating compliance shall be demonstrated to the Principal Certifying Authority, prior to the issue of any Occupation Certificate.

(Reason: Adequate access and egress.)

70. DRAINAGE SYSTEM - MAINTENANCE OF EXISTING SYSTEM (OC)

Where elements of the existing drainage system are to be utilised, the existing drainage system shall be overhauled and maintained clear of silt and accumulated debris. Silt and the like shall be removed, not flushed from the system.

A certificate shall be provided by a suitably qualified person (a registered plumber or a person of equivalent or greater experience or qualification) to the satisfaction of the Principal Certifying Authority, prior to the issue of any Occupation Certificate to confirm that the system is in good working order and adequate to accept additional flows having regard to any relevant standards and/or Sydney Water requirements.

(Reason: Maintenance and environment.)

71. **ENGINEERING WORKS (CERTIFICATION OF)**

Prior to occupation of the premises, a Work As Executed (WAE) Plan of all engineering and/or drainage works is to be submitted to the Principal Certifying Authority. The WAE Plan is to be certified by a suitably Qualified Engineer, with Corporate Membership standing in the Institution of Engineers Australia and registered on the National Professional Engineers Register (NPER) under the appropriate professional category, demonstrating that:

- i) the stormwater drainage system; and/or
- ii) the car parking arrangement and area; and/or
- iii) any related footpath crossing works; and/or
- iv) the proposed basement pump and well system; and/or
- v) the proposed driveway and layback; and/or
- vi) any other civil works

have been constructed in accordance with the approved plans and any relevant Standards and Council policies/specifications.

For major works, such as subdivisions, works within the road reserve (requiring separate S138 approval) and as where specified by Council, a Part 4A Certificate will be required. It is strongly recommended that an Engineer supervise all engineering related works.

Where Council is not the Principal Certifying Authority, an electronic copy of the above documents is to be provided to Council, prior to the issue of any Occupation Certificate.

(Reason: Asset management.)

72. **FIRE SAFETY CERTIFICATION (OC)**

A fire safety certificate shall be obtained in accordance with Part 9, Division 4 of the Environmental Planning and Assessment Regulation 2000, prior to the issue of any Occupation Certificate.

An fire safety certificate is a certificate issued by the owner of a building to the effect that each essential fire safety measure specified in the current fire safety schedule for the part of the building to which the certificate relates:

- i) has been assessed by a properly qualified person; and
- ii) was found, when it was assessed, to be capable of performing to at least the standard required by the current fire safety schedule for the building for which the certificate is issued.

An interim fire safety certificate must be provided before an interim occupation certificate can be used for a building under Clause 153(2) of the Environmental Planning & Assessment Regulation 2000.

A final fire safety certificate must be provided before an interim occupation certificate can be used for a building under Clause 153(1) of the Environmental Planning & Assessment Regulation 2000.

A copy of the fire safety certificate and fire safety schedule shall be:

- i) submitted to Strathfield Council;
- ii) submitted to the Commissioner of the New South Wales Fire Brigade; and
- iii) prominently displayed in the building.

(Reason: Fire safety and statutory requirement.)

73. LANDSCAPING - ARBORIST'S FOLLOW UP REPORT OF TREE/S TO BE RETAINED (OC)

As part of the on-going assessment of the tree/s to be retained, the consulting arborist engaged by the applicant is to assess their health and any impacts suffered by them as a result of the proposed approved development, prior to the issue of an Occupation Certificate. Findings are to be compiled in a detailed report and submitted to the Principle Certifying Authority, which documents the following:

- i) methods of excavation or construction used to carry out the works;
- ii) any damage sustained by the tree/s as a result of the works;
- iii) any subsequent remedial works required to be carried out by the consulting arborist as a result of the damage; and
- iv) any future or on-going remedial work required to be carried out to ensure the long term retention of the tree/s.

(Reason: To ensure the survival of trees to be retained.)

74. OCCUPATION OF BUILDING (OC)

A person must not commence occupation or use (or change of use where an existing building) of the whole or any part of a new building (within the meaning of section 109H (4) of the Act) unless an Interim Occupation Certificate or Final Occupation Certificate has been issued in relation to the building or part.

The Principal Certifying Authority is required to be satisfied, amongst other things, that:

- i) all required inspections (including each applicable mandatory critical stage inspection) have been carried out; and
- ii) any preconditions to the issue of the certificate required by a development consent have been met.

Note: New building includes an altered portion of, or an extension to, an existing building.

(Reason: Statutory requirement.)

75. STORMWATER - CERTIFICATION OF THE CONSTRUCTED DRAINAGE SYSTEM (OC)

The constructed stormwater system shall be certified by a suitably qualified person, in accordance with Council's Stormwater Management Code, prior to the issue of any

Occupation Certificate.

(Reason: Adequate stormwater management.)

76. STORMWATER - COVENANT AND RESTRICTION AS TO USER FOR STORMWATER CONTROLLED SYSTEMS (OC)

Prior to the issue of any Occupation Certificate, the applicant shall register a Positive Covenant and a Restriction as to User under section 88E and or section 88B of the Conveyancing Act as appropriate in favour of Council, ensuring the ongoing retention, maintenance and operation of the stormwater facility on-site detention and water sensitive urban design components.

Where any drainage line or service conduit is to traverse any property other than that which it serves, an appropriate easement will be required. In this case, the applicant shall register an easement no less than 1200mm wide over the proposed drainage line or service concurrently with any subdivision registration.

The wording on the 88B Instrument is to make reference to the Council file where the Construction plans and the Work As Executed (as built), plans are held. Typical wording can be obtained from Council's Specification for the Management of Stormwater document.

(Reason: To ensure the on-site detention and/or pump system is maintained to an appropriate operational standard.)

77. SUBDIVISION - EVIDENCE OF CONSOLIDATION (OC)

The existing allotments shall be consolidated into a single lot. Evidence that the plan of consolidation has been registered as a deposited plan with the Land and Property Information Office must be submitted to Council, prior to occupation of the site.

(Reason: Proper management of land.)

78. VENTILATION SYSTEMS – MECHANICAL (OC)

The mechanical ventilation system is to comply with the following:

- i) The Building Code of Australia;
- ii) Protection of the Environment Operations Act 1997; and
- iii) Australian Standard AS1668-1991.

In addition, odour control measures, such as activated carbon or catalytic oxidisers, must be used to treat ventilation gases prior to discharge. The method of odour control must be designed by a suitably qualified mechanical ventilation engineer.

At the completion of the installation of the mechanical exhaust ventilation system, a certificate from a practising mechanical engineer shall be submitted to the Principal Certifying Authority, prior to issue of the Occupation Certificate demonstrating compliance with the above.

(Reason: To ensure the mechanical exhaust ventilation system complies with the relevant requirements/standards.)

79. VENTILATION SYSTEMS – NATURAL (OC)

The natural ventilation system shall be designed, constructed and installed in accordance with the provisions of:

- i) The Building Code of Australia; and
- ii) Protection of the Environment Operations Act 1997.

Details demonstrating compliance with this condition shall be submitted to the Principal Certifying Authority, prior to issue of the Occupation Certificate.

(Reason: To ensure any natural ventilation systems comply with the relevant regulations/standards.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A SUBDIVISION CERTIFICATE (SC)

80. COMMENCEMENT OF SUBDIVISION WORKS - REQUIREMENTS PRIOR TO (SC)

Subdivision work in accordance with a consent must not commence until:

- i) a Construction Certificate has been issued;
- ii) the person having the benefit of the development consent has appointed the Principal Certifying Authority (PCA);
- iii) the PCA (if not Council) has, no later than two (2) days before the subdivision work commences, notified the Council (or other consent authority where applicable) of the PCA's appointment; and
- iv) the person having the benefit of the consent has given at least two (2) day's notice to the Council of the person's intention to commence the subdivision work.

NB: Crown work certified in accordance with s109R of the Environmental Planning and Assessment Act 1979 is exempted from the above requirements.

(Reason: Statutory requirements.)

81. SEPARATE APPLICATION FOR STRATA SUBDIVISION (SC)

This consent does not imply approval to create a separate title, by subdivision or otherwise. Should it be intended to subdivide the approved development into strata title allotments, Council will require the lodgement of a separate development application for consideration.

(Reason: To ensure compliance with the consent.)

82. SUBDIVISION CERTIFICATE - REQUIREMENTS PRIOR TO THE ISSUE OF (SC)

A Subdivision Certificate allows a person to lodge a plan of subdivision with NSW Land and Property Information (LPI). The plan of subdivision identifies each of the allotments approved under the original consent (if required) or each allotment subject to an exempt boundary adjustment. The plan of subdivision is required to be prepared by a registered surveyor.

All types of subdivision (Torrens, Strata and Community Title) are required to be registered with NSW LPI before a new 'allotment' of a subdivision of land can be created.

The release of a Subdivision Certificate confirms that the Principal Certifying Authority (Council or Accredited Certifier) is satisfied that works are completed in accordance with the applicable Development Consent and that the land is suitable to occupy.

Prior to the issuing of any Subdivision Certificate under section 37A of the Strata Schemes (Freehold Development) Act 1973, and section 66A of the Strata Schemes (Leasehold Development) Act 1986, and in accordance with section 29A of the Strata Schemes

(Freehold Development) Regulation 2007 and section 30A of the Strata Schemes (Leasehold Development) Regulation 2007, the PCA is required to be satisfied that:

- i) the floors, external walls and ceilings depicted in the proposed strata plan for the building correspond to those of the building as constructed;
- ii) the floors, external walls and ceilings of the building as constructed correspond to those depicted in the building plans that accompanied the construction certificate for the building; and
- iii) any facilities required by the relevant development consent (such as parking spaces, terraces and courtyards) have been provided in accordance with those requirements.

As construction of the building nears completion, or after it has been completed, the Principal Certifying Authority must inspect the building and the common property areas around the building, so as to be satisfied, as required by section 66AA of the Act, that the above requirements have been met.

The Principal Certifying Authority shall also be satisfied that:

- i) all required inspections (including each applicable mandatory critical stage inspection) have been carried out; and
- ii) any preconditions to the issue of the certificate required by a development consent or complying development certificate have been met.

The Subdivision Certificate must not be issued until the Principal Certifying Authority has issued the Final Occupation Certificate in relation to the approved development.

(Reason: Statutory requirements.)

83. SUBDIVISION - LODGEMENT OF FINAL PLAN OF SUBDIVISION (SC)

Once a Subdivision Certificate is issued by the Principal Certifying Authority, the Final Plan of Subdivision must be registered with Land and Property Information. Documentary evidence that the linen plan has been registered with Land and Property Information must be submitted to Strathfield Council as soon as practicable.

(Reason: Statutory requirement.)

84. SYDNEY WATER - SECTION 73 CERTIFICATE (SC)

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained before the issue of the Subdivision Certificate. An application must be made through an authorised Water Servicing Coordinator (refer www.sydneywater.com.au).

Following receipt of the application a 'Notice of Requirements' will be issued detailing water and sewer extensions to be built and charges to be paid. Please make early contact with the Water Servicing Coordinator, as building of water/sewer extensions can be time consuming and may impact on other services and building, driveway or landscape design.

Sydney Water written advice that you have obtained the Notice of Requirements must be submitted to the Principal Certifying Authority

The Section 73 Compliance Certificate must be submitted to the Principal Certifying Authority prior to release of the Subdivision Certificate /any occupation of the premises.

(Reason: To comply with the statutory requirements of Sydney Water.)

85. UTILITIES - ELECTRICITY SUBSTATION DEDICATION AS ROAD AND/OR EASEMENT FOR ACCESS (SC)

Where an electricity substation is provided on the site adjoining the road boundary, the area within which the electricity substation is located must be dedicated as public road, free of cost to Council. The size and location of the electricity substation is to be in accordance with the requirements of the appropriate energy authority and Council. The opening of any access doors shall not intrude onto any public road (footway or road pavement).

Where access to the electricity substation is required from a public place and across the site, an easement for access across the site from the public place must be created upon the final plan of subdivision burdening the subject site and benefiting the Crown in right of New South Wales and any Statutory Corporation requiring access to the electricity substation.

The above details must be included on the final plan of subdivision, prior to the release of the Subdivision Certificate.

(Reason: Formalisation of access to utility.)

CONDITIONS TO BE SATISFIED DURING ONGOING USE OF THE PREMISES (OU)**86. VISITOR PARKING RESTRICTION (OU)**

All visitor parking spaces must not at any time be allocated sold or leased to an individual owner/occupier and must be strictly retained as common property by the Owners Corporation.

(Reason: Compliance with approved visitor parking provision.)

87. VISITOR PARKING RESTRICTION (OU)

All visitor parking spaces must not at any time be allocated sold or leased to an individual owner/occupier and must be strictly retained as common property by the Owners Corporation.

(Reason: Compliance with approved visitor parking provision.)

RESOLUTION

We find the Clause 4.6 variation to be well founded and approve of the application as a **DEFERRED COMMENCEMENT CONSENT** with the deletion of D1 (Building Separation).

FOR: P.Stein, B.Kirk, V.Albin, P.Smith

AGAINST: Nil

Reasons: The Panel generally agrees with the planning officer's report and notes that the proposal is in accordance with the Objectives and Aims of the LEP. The Panel notes that in relation to the deletion of D1 (Building Separation), the proposed separation is satisfactory given the context and setting.

The panel received a number of submissions, including at the public meeting, and took these into account in coming into its decision.

**** End Minutes - Report No. 1****

TO: Strathfield Local Planning Panel Meeting - 1 March 2018
REPORT: SLPP – Report No. 2
SUBJECT: (S82A)
DA2017/070/01- 88 HOMEBUSH ROAD, STRATHFIELD
LOT 1 DP 309287

DA NO. DA2017/070/01

RECOMMENDATION

That Development Application DA2017/070/01, S82A Review for demolition of existing structures and construction of a two (2) storey boarding house with basement parking at 88 Homebush Road, Strathfield be **AFFIRMED BY A REFUSAL**, for the following reasons:

1. The proposal fails to satisfy the character test requirement under Clause 30A of the ARHSEPP in that the design is not compatible with the character of the local area due to the unacceptable likely impacts on the adjoining heritage item to the north, the lack of articulation to the northern side elevation; the height of the finished ground floor levels which are raised well above natural ground level and the lack of the contribution to the streetscape (*Section 79C(1)(a)(i) of the Environmental Planning and Assessment Act 1979*).
2. The proposal is considered to be unsatisfactory having regard to the dominance of the rear carparking area, inconsistent with the location of onsite carparking for residential development in the locality. The carparking area has an adverse impact on the neighbours to the East and North. The carparking area also reduces the landscape open space in the rear of the proposal. (*Section 79C(1)(b) of the Environmental Planning and Assessment Act 1979*).
3. The proposal fails to satisfy the objectives of Clause 1.2 (2) (a) of the Strathfield Local Environmental Plan 2012 which seeks to ensure a high quality built form by ensuring that new development exhibits design excellence and reflects the existing or desired future character of the Homebush Road streetscape. (*Section 79C(a)(i) of the Environmental Planning and Assessment Act 1979*).
4. The proposal fails to satisfy the objectives of Clause 1.2 (2) (f) and provisions under Clause 5.10 of the Strathfield Local Environmental Plan 2012 which requires heritage items including associated fabric, settings and views, to be conserved. The proposal is incompatible with the prevailing height, bulk and scale of surrounding heritage dwellings (item I115 in particular). The proposed development impinges upon the visual curtilage established around the northern adjoining heritage dwelling and is of direct contrast to the traditional-style dwellings in the streetscape which are predominantly single storey (*Section 79C(a)(i) of the Environmental Planning and Assessment Act 1979*).
5. The proposed development makes insufficient provision for the onsite storage and management of waste in accordance with the requirements of Part H of the Strathfield Consolidated Development Control Plan 2005 (*Section 79C(a)(iii) of the Environmental Planning and Assessment Act 1979*).
6. The proposed development fails to provide a satisfactory method of Stormwater disposal from the site. (*Section 79C(1)(c) of the Environmental Planning and Assessment Act 1979*).
7. The Propose development is not in the public interest. (*Section 79C(1)(e) of the Environmental Planning and Assessment Act 1979*).

RESOLUTION

That Development Application DA2017/070/01, S82A Review for demolition of existing structures and construction of a two (2) storey boarding house with basement parking at 88 Homebush Road, Strathfield be **AFFIRMED BY A REFUSAL**.

FOR: P.Stein, B.Kirk, V.Albin, P.Smith

AGAINST: Nil

**** End Minutes - Report No. 2****

TO: Strathfield Local Planning Panel Meeting - 1 March 2018
REPORT: SLPP – Report No. 3
SUBJECT: DA2017/162- 72-73 THE CRESCENT, HOMEBUSH
 LOT 5 IN DP 6479
DA NO. 2017/162

RECOMMENDATION

That Development Application No. 2017/162 for the demolition of existing structures and construction of a two (2) storey boarding house development with (16) lodger rooms under the *Affordable Rental Housing SEPP 2009* at 72-73 The Crescent, Homebush be **APPROVED**, subject to the following conditions:

SPECIAL CONDITIONS (SC)

1. VISUAL PRIVACY (SC)

The two (2) upper level south facing living room windows pertaining to Rooms 13 and 14 are to be redesigned as either highlight windows with a sill height of 1.7m from the floor or provided with fixed privacy louvers capable of precluding views to the southern adjoining site. Details demonstrating compliance with this requirement shall be submitted to and approved by a Principle Certifying Authority **prior to the issue of a Construction Certificate.**

(Reason: Protect residential amenity)

2. UPPER ROOF LEVEL (SC)

The planter boxes located upon the roof of the development fronting Mackenzie Street are to be removed so as to ensure the roof remains as a non-trafficable roof area.

(Reason: Protect residential amenity)

3. ACOUSTIC REPORT (SC)

An Acoustic Assessment Report was prepared by Koikas Acoustics and submitted during the assessment process having consideration for the abovementioned requirements. A condition of consent is therefore recommended to ensure compliance with the recommendations made under Section 7 of the report so as to ensure future residents will not be adversely affected by the adjoining rail corridor.

(Reason: Protect residential amenity)

GENERAL CONDITIONS (GC)

4. APPROVED PLANS AND REFERENCE DOCUMENTATION (GC)

The development, except where modified by a condition(s) of consent, is to be carried out in accordance with the following plans and reference documentation:

Plans affixed with Council's 'Development Consent' stamp relating to Development Consent No. 2017/162:

Drawing No.	Title/Description	Prepared by	Issue /	Date received
-------------	-------------------	-------------	---------	---------------

			Revision & Date	by Council
DA-102	Demolition Plan	Manor House Design	A	10 November 2017
DA- 201	Ground Floor Plan	Manor House Design	B	15 January 2018
DA-202	First Floor Plan	Manor House Design	B	15 January 2018
DA-203	Roof Plan	Manor House Design	B	15 January 2018
DA-301	North & West Elevation Plan	Manor House Design	B	15 January 2018
DA-302	South & East Elevation Plan	Manor House Design	B	15 January 2018
DA-401	Cross Section A Plan	Manor House Design	B	15 January 2018
DA-304	Fence Elevation Plan	Manor House Design	A	15 January 2018
DA-601	Schedule of External Finishes	Manor House Design	B	15 January 2018
L-01	Landscape Plan	RFA Landscape Architects	A	10 November 2017
STW-05	Sediment and Erosion Control Plan	Hydraulic Services	01	10 November 2017
STW-01	Stormwater Drainage Concept Plan	Hydraulic Services	02	12 February 2018

Reference Documentation affixed with Council's 'Development Consent' stamp relating to Development Consent No. 2017/162:

Title / Description	Prepared by	Issue/Revision & Date	Date received by Council
Statement of Environmental Effects	James Kim	November 2017	10 November 2017
Statement of Heritage Impact	James Kim	November 2017	10 November 2017
Plan of Management	James Kim	November 2017	10 November 2017
Waste Management Plan	-	-	10 November 2017
Acoustic Assessment	Koikas Acoustics Pty Ltd	8 th February 2018 – Revision 1	12 February 2018

In the event of any inconsistency, the conditions of this consent shall prevail.

(Reason: To ensure that the form of the development undertaken is in accordance with the determination of Council.)

5. BOARDING HOUSE - APPROVED USE (GC)

This approval is granted for the use of the land for the purposes of a Boarding House comprising a maximum of 16 Boarding rooms. . This includes (16) single rooms (maximum 1 person per room). No double rooms are permitted.

All lodgers shall be required to reside on the premises for a minimum period of three (3) months in accordance with the definition of a Boarding House under the Strathfield Local Environmental Plan 2013.

The approved boarding house must operate within the definition of 'boarding house' under *SLEP 2012*. The approved boarding house cannot be strata or community title subdivided.

(Reason: To clarify the terms of the approval and to control the maximum number of lodgers living in the premises at any one time.)

6. BUILDING HEIGHT - MAXIMUM RL TO BE COMPLIED WITH (GC)

The height of the building shall be reduced in height by 1m. As measured from Australian Height Datum (AHD), the building must not exceed Relative Level (RL) 20.01AHD to the roof ridge of the western wing of the building.

(Reason: To ensure the approved building height is complied with.)

7. CONSTRUCTION HOURS (GC)

No construction or any other work related activities shall be carried out on the site outside the hours of 7.00 am to 5.00 pm Mondays to Fridays and 8am to 1pm Saturdays.

No building activities are to be carried out at any time on a Sunday or public holiday.

Where the development involves the use of jackhammers/ rock breakers and the like or other heavy machinery, such equipment may only be used between the hours of 7.00 am - 5.00 pm Monday to Friday only.

(Reason: To maintain amenity to adjoining land owners.)

8. CONSTRUCTION WITHIN BOUNDARIES (GC)

The development including but not limited to footings, walls, roof barges and guttering must be constructed wholly within the boundary of the premises. No portion of the proposed structure shall encroach onto the adjoining properties. Gates must be installed so they do not open onto any footpath or adjoining land.

(Reason: Approved works are to be contained wholly within the subject site.)

9. DEMOLITION – GENERALLY (GC)

Alteration and demolition of the existing building is limited to that documented on the approved plans (by way of notation). No approval is given or implied for removal and/or rebuilding of any portion of the existing building which is not shown to be altered or demolished.

(Reason: To ensure compliance with the approved development.)

10. DEMOLITION - SITE SAFETY FENCING (GC)

Site fencing is to be erected to a minimum height of 1.8m complying with WorkCover

Guidelines, to exclude public access to the site, prior to any demolition works occurring and maintained for the duration of the demolition works.

If applicable, a separate Hoarding Application for the erection of an A class (fence type) or B class (overhead type) hoarding along the street frontage(s) complying with WorkCover requirements must be obtained including:

- payment to Council of a footpath occupancy fee based on the area of footpath to be occupied and Council's Schedule of Fees and Charges before the commencement of work; and
- provision of a Public Risk Insurance Policy with a minimum cover of \$10 million in relation to the occupation of and works within Council's road reserve, for the full duration of the proposed works, must be obtained with a copy provided to Council.

(Reasons: Statutory requirement and health and safety.)

11. FENCING - FRONT FENCE HEIGHT (GC)

The front and side fencing (including the building line to a secondary street frontage on a corner site) shall not exceed a height of 1m above natural ground level.

(Reason: To ensure a positive contribution to the streetscape in accordance with the Strathfield Consolidated DCP 2005.)

12. LANDSCAPING - IRRIGATION OF COMMON AND PRIVATE LANDSCAPE AREAS (GC)

All common and private landscape areas including all planters of new multi-unit, commercial, mixed-use and industrial development are to have full coverage by a fully automatic irrigation system. The design, materials and installation are to be in accordance with Sydney Water Codes and satisfy all relevant Australian Standards. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior occupation of the premises.

(Reason: To ensure appropriate landscape maintenance.)

13. LANDSCAPING - TREES PERMITTED TO BE REMOVED (GC)

The following listed trees are permitted to be removed to accommodate the proposed development:

Tree	Height/ Spread (m)	Location
All trees within the property boundary	-	The subject site

All trees permitted to be removed by this consent shall be replaced by species selected from Council's Recommended Tree List.

Replacement trees shall be a minimum 50 litre container size. Trees are to conform to the NATSPEC guide and Guide for assessing the quality of and purchasing of landscape trees by Ross Clarke, 2003. Trees are to be true to type, healthy and vigorous at time of delivery and planting, shall be pest and disease free, free from injury and wounds and self-supporting; and shall be maintained until maturity.

All trees are to be staked and tied with a minimum of three (3) hardwood stakes. Ties are to be hessian and fixed firmly to the stakes, one tie at half the height of the main stem, others

as necessary to stabilise the plant.

Root deflection barriers having a minimum depth of 600mm are to be installed adjacent to all footpaths and driveways.

Soil conditioner/fertilizer/moisture retention additive/s are to be applied in accordance with manufacturer's recommendations, and mixed into the backfilling soil after planting tree/s.

A minimum 75mm depth of organic mulch shall be placed within an area 0.5m from the base of the tree.

Details demonstrating compliance shall be demonstrated to the Principal Certifying Authority, prior to the issue of any Occupation Certificate.

(Reason: To ensure appropriate planting back onto the site.)

14. LANDSCAPING - TREE PRESERVATION (GC)

All street trees and trees on private property that are protected under Council's controls, shall be retained except where Council's prior written consent has been obtained. The felling, lopping, topping, ringbarking, wilful destruction or removal of any tree/s unless in conformity with this approval or subsequent approval is prohibited. This applies to the following trees:

<u>Tree</u>	<u>Height/ Spread (m)</u>	<u>Location</u>	<u>Protecti on Zone (m)</u>	<u>Structural Root Zone (m)</u>
1)Lophostemon confertus	5 x 8	Road reserve	6.0	2.57
2)Lophostemon confertus	5 x 8	Road reserve	6.0	2.57
3)Lophostemon confertus	5 x 8	Road reserve	6.0	2.57
4)Lophostemon confertus	5 x 8	Road reserve	6.0	2.57
5)Lophostemon confertus	5 x 8	Road reserve	6.0	2.57
6)Salix sp.	10 x 5	Adjoining	4.8	2.47
7)Araucaria sp.	10 x 3	Adjoining	4.8	2.47

All healthy trees and shrubs identified for retention on the approved drawings are to be suitably protected in accordance with Australian Standard AS4970 – Protection of Trees on Development prior to the commencement of any works (including any demolition and excavation) and maintained for the duration of the works.

Manual excavation is required within the canopy spread of the retained trees referred to in table above.

(Reason: To ensure the protection of trees to be retained on the site.)

15. LIGHTING (GC)

Any lighting of the premises shall be installed and maintained in accordance with Australian Standard AS 4282-1997: Control of the Obtrusive Effects of Outdoor Lighting so as to avoid annoyance to the occupants of adjoining premises or glare to motorists on nearby roads.

No flashing, moving or intermittent lighting, visible from any public place may be installed on the premises or external signage associated with the development, without the prior approval of Council.

(Reason: To protect the amenity of surrounding development and protect public safety.)

16. MATERIALS – CONSISTENT WITH SUBMITTED SCHEDULE (GC)

All external materials, finishes and colours are to be consistent with the schedule submitted and approved by Council with the development application.

(Reason: To ensure compliance with this consent.)

17. PRINCIPAL CERTIFYING AUTHORITY (PCA) IDENTIFICATION SIGN (GC)

Prior to commencement of any work, signage must be erected in a prominent position on the work site identifying:

- i) the Principal Certifying Authority (PCA) by showing the name, address and telephone number of the PCA;
- ii) the Principal Contractor by showing the Principal Contractor's name, address and telephone number (outside of work hours) for that person; and
- iii) the sign must state that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the work is being carried out, but must be removed when the work has been completed.

This clause does not apply to building work, subdivision work or demolition work that is carried out inside an existing building that does not affect the external walls of the building.

(Reason: Statutory requirement.)

18. PRIVACY - SCREEN PLANTING TO SIDE AND REAR BOUNDARIES (GC)

Evergreen shrubs with a minimum 5 litre container size achieving a minimum mature height of 3m shall be planted along the side and rear boundaries to provide suitable privacy screening. Screen planting shall be maintained at all times. Details of the selected plants shall be submitted to and approved by the Principal Certifying Authority. Compliance with this condition shall be certified by the Principal Certifying Authority, prior to occupation of the premises.

(Reason: To maintain privacy amenity to neighbouring residences.)

19. SITE MANAGEMENT (DURING DEMOLITION AND CONSTRUCTION WORKS)

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standard AS 2601-2001.
- ii) Demolition must be carried out by a registered demolition contractor.
- iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out.
- iv) No blasting is to be carried out at any time during construction of the building.
- v) Care must be taken during demolition/ excavation/ building/ construction to prevent

- any damage to adjoining buildings.
- vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
 - vii) Any demolition and excess construction materials are to be recycled wherever practicable.
 - viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
 - ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997. All excavated material should be removed from the site in an approved manner and be disposed of lawfully to a tip or other authorised disposal area.
 - x) All waste must be contained entirely within the site.
 - xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
 - xii) All materials on site or being delivered to the site are to generally be contained within the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.
 - xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts, etc.) should be kept on site as evidence of approved methods of disposal or recycling.
 - xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
 - xv) Public footways, include nature strips and roadways adjacent to the site must be maintained and cleared of obstructions during construction. No building materials, waste containers or skips may be stored on the road reserve or footpath without prior separate approval from Council, including payment of relevant fees.
 - xvi) Building operations such as brick-cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
 - xvii) All site waters during excavation and construction must be contained on site in an approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.
 - xviii) Any work must not prohibit or divert any natural overland flow of water.
 - xix) Toilet facilities for employees must be provided in accordance with WorkCover NSW.
 - xx) Protection pads are to be installed to the kerb and gutter where trucks and vehicles enter the site.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

20. **STORMWATER MANAGEMENT PLAN - CERTIFICATION REQUIREMENT (GC)**

A detailed Stormwater Management Plan (SWMP) in line with Council's Stormwater Management Code is to be prepared and certified by a practicing Chartered Professional Engineer on the National Professional Engineer's Register (NPER) at Engineers Australia and submitted to the Principal Certifying Authority and Council, prior to the issue of a Construction Certificate. The SWMP is to be based on the approved development as modified by any conditions of consent.

(Reason: To ensure appropriate provision is made for the disposal and management of stormwater generated by the development, and to ensure public infrastructure in Council's care and control is not overloaded.)

21. SYDNEY WATER - STAMPED PLANS PRIOR TO COMMENCEMENT (GC)

The approved plans must be submitted to a Sydney Water Quick Check agent or Customer Centre to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Plans will be appropriately stamped.

For Quick Check agent details please refer to the web site www.sydneywater.com.au (see Building Developing and Plumbing then Quick Check) or telephone 13 20 92. The consent authority or a Certifying Authority must ensure that a Quick Check agent/Sydney Water has stamped the plans before the commencement of work.

(Reason: Compliance with Sydney Water requirements.)

22. UTILITIES AND SERVICES - PROTECTION OF (GC)

Any footings or excavation to be located or undertaken adjacent to Council's stormwater must be designed to address the following requirements:

- i) all footings and excavation must be located wholly within the site and clear of any easement boundaries;
- ii) all footings and excavation must be located a minimum of 1000mm from the centreline of the pipeline or 500mm from the outside of the pipeline, whichever is the greater distance from the centreline; and
- iii) footings must extend to at least the depth of the invert of the pipeline unless the footings are to be placed on competent bedrock.

If permanent excavation is proposed beneath the obvert of the pipeline, suitable means to protect the excavation and proposed retaining structures from seepage or other water flow from the pipeline and surrounding subsoil, must be provided. The design must be prepared by a qualified practicing Structural/Civil Engineer.

Construction plans must be approved by the appropriate utility's office (e.g. council, Sydney Water Corporation) to demonstrate that the development complies with the utility's requirements.

The applicant must provide written evidence (e.g. compliance certificate, formal advice) of compliance with the requirements of all relevant utility providers (e.g. Water, Energy, Telecommunications, Gas).

(Reason: To ensure protection of Council assets.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A CONSTRUCTION CERTIFICATE (CC)

23. ACCESS - ACCESS FOR PEOPLE WITH DISABILITIES (CC)

Access for people with disabilities must be provided in accordance with the requirements of the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

24. ACCESS - DISABLED TOILETS (CC)

Plans and details of the disabled toilet/s complying with the relevant Australian Standards, the Building Code of Australia, and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

25. BICYCLE STORAGE PROVISION (CC)

On-site provision for bicycle storage facilities shall be in accordance with the Strathfield Consolidated Development Control Plan 2005. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Compliance with SCDCP 2005 and to encourage sustainable transport options.)

26. BOARDING HOUSE - CONSTRUCTION OF (CC)

The construction of the boarding house shall comply with all applicable legislation/regulation and standards, including:

- i) Boarding Houses Act 2012;
- ii) Boarding Houses Regulation 2013;
- iii) Local Government Act 1993; and
- iv) Local Government Regulation 2005.

Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior to occupation of the premises.

(Reason: To ensure compliance with relevant legislation.)

27. BUILDING CODE OF AUSTRALIA - COMPLIANCE WITH (CC)

All architectural drawings, specifications and related documentation shall comply with the Building Code of Australia (BCA). All work must be carried out in accordance with the requirements of the Building Code of Australia (BCA).

In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of that Act, such a contract of insurance is to be in force before any building work authorised to be carried out by the consent commences.

Details demonstrating compliance with this condition are to be submitted to the Principle Certifying Authority, prior to issue of the Construction Certificate.

(Reason: This is a 'prescribed' condition under clause 98(1) of the Environmental Planning and Assessment Regulation 2000.)

28. CAR PARKING - DISABLED CAR PARKING SPACES (CC)

One (1) of the car parking spaces provided as part of the total requirement shall be reserved for disabled persons. These spaces shall be a minimum of 2.4m wide x 5.4m long and located near pedestrian access routes designed for disabled persons. Each space shall be clearly marked as such. A shared area 2.4 m wide x 5.4m long shared area should be provided. Bollard shall be placed in this shared area.

Car parking for people with disabilities shall be provided in accordance with the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Prior to the issue of a Construction Certificate, the plans shall be notated to demonstrate compliance.

The above details shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate.

(Reason: To ensure adequate parking for persons with a disability.)

29. CAR PARKING - COMPLIANCE WITH AS/NZS 2890.1:2004 (CC)

Car parking dimensions must comply with the Australian/New Zealand Standard AS/NZS 2890.1:2004 - Parking facilities - Off-street car parking. Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To ensure compliance with Australian Standards relating to parking of vehicles.)

30. CAR PARKING - VEHICULAR CIRCULATION, AISLE AND RAMP WIDTHS (CC)

The aisle widths, internal circulation, ramp widths and grades of the car park shall comply with the Roads and Traffic Authority Guidelines and AS/NZS 2890.1:2004 - Off-Street Car Parking Code.

Vehicular manoeuvring paths are to be prepared demonstrating that all vehicles can enter or depart the site in a forward direction without encroaching on required car parking spaces.

(Reason: To ensure compliance with Australian Standards relating to manoeuvring, access and parking of vehicles.)

31. CAR PARKING - VEHICULAR CROSSING WIDTH AT PROPERTY BOUNDARY (CC)

The width of the existing vehicular crossing fronting Mackenzie Street is to remain unchanged. Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Compliance with SCDCP 2005.)

32. COMMENCEMENT OF WORKS (NO WORKS UNTIL A CC IS OBTAINED)

Building work, demolition or excavation must not be carried out until a Construction Certificate has been issued by either Strathfield Council or a Principal Certifying Authority.

Demolition of any part of a building triggers 'commencement of erection of building' pursuant of section 81A(2) of the EP&A Act 1979. Accordingly, demolition works must not commence until a Construction Certificate has been issued, a Principal Certifying Authority has been appointed and a Notice of Commencement has been issued.

(Reason: To ensure compliance with statutory provisions.)

33. **CONSTRUCTION AND ENVIRONMENTAL MANAGEMENT PLAN (CC)**

The applicant must prepare and submit a Construction and Environmental Management Plan (CEMP) to the Principal Certifying Authority, including:

- i) Detailed information on any approvals required from other authorities prior to or during construction.
- ii) Traffic management, including details of:
 - ingress and egress of vehicles to the site;
 - management of loading and unloading of materials;
 - the location of heavy vehicle parking off-site; and
 - designated routes for vehicles to the site.
- iii) The proposed areas within the site to be used for a builder's site office and amenities, the storage of excavated material, construction materials and waste containers during the construction period.
- iv) Erosion and sediment control, detailing measures and procedures consistent with the requirements of Council's guidelines for managing stormwater, including:
 - the collection and treatment of stormwater and wastewater generated on site prior to discharge; and
 - procedures to prevent run-off of solid material and waste from the site.
- v) Waste management, including:
 - details of the types and estimated volumes of waste materials that will be generated;
 - procedures for maximising reuse and recycling of construction materials; and
 - details of the off-site disposal or recycling facilities for construction waste.
- vi) Dust control, outlining measures to minimise the generation and off-site transmission of dust and fine particles, such as watering or damp cloth fences.
- vii) A soil and water management plan, which includes:
 - measures to minimise the area of soils exposed at any one time and conserve top soil;
 - identification and protection of proposed stockpile locations;
 - preservation of existing vegetation and revegetation;
 - measures to prevent soil, sand, sediments leaving the site in an uncontrolled manner;
 - measures to control surface water flows through the site in a manner that diverts clean run-off around disturbed areas, minimises slope gradient and flow distance within disturbed areas, ensures surface run-off occurs at non-erodible velocities, and ensures disturbed areas are promptly rehabilitated;
 - details of sediment and erosion control measures in place before work commences;
 - measures to ensure materials are not tracked onto the road by vehicles entering or leaving the site; and
 - details of drainage to protect and drain the site during works.
- viii) Asbestos management procedures:
 - Anyone who removes, repairs or disturbs bonded or a friable asbestos material

must hold a current removal licence from Workcover NSW holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal License which ever applies and a current WorkCover Demolition License where works involve demolition. To find a licensed asbestos removalist please see www.workcover.nsw.gov.au

- Removal of asbestos by a person who does not hold a Class A or Class B asbestos removal license is permitted if the asbestos being removed is 10m² or less of non-friable asbestos (approximately the size of a small bathroom). Friable asbestos materials must only be removed by a person who holds a current Class A asbestos license.
- Before starting work, a work site-specific permit approving each asbestos project must be obtained from Workcover NSW. A permit will not be granted without a current Workcover licence. All removal, repair or disturbance of or to asbestos material must comply with the following:
 - The Work Health and Safety Act 2011;
 - The Work Health and Safety Regulation 2011;
 - How to Safety Remove Asbestos Code of Practice – WorkCover 2011; and
 - Safe Work Australia Code of Practice for the Management and Control of Asbestos in the Workplace.
- Following completion of asbestos removal works undertaken by a licensed asbestos removalist re-occupation of a workplace must not occur until an independent and suitably licensed asbestos removalist undertakes a clearance inspection and issues a clearance certificate.
- The developer or demolition contractor must notify adjoining residents at least two (2) working days (i.e. Monday to Friday exclusive of public holidays) prior to the commencement of asbestos removal works. Notification is to include, at a minimum:
 - the date and time when asbestos removal works will commence;
 - the name, address and business hours contact telephone number of the demolisher, contractor and/or developer;
 - the full name and license number of the asbestos removalist/s; and
 - the telephone number of WorkCover's Hotline 13 10 50
 - warning signs informing all people nearby that asbestos removal work is taking place in the area. Signs should be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs should be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs should be in accordance with AS 1319-1994 Safety signs for the occupational environment for size, illumination, location and maintenance; and
 - appropriate barricades installed as appropriate to prevent public access and prevent the escape of asbestos fibres. Barricades must be installed prior to the commencement of asbestos removal works and remain in place until works are completed.

(Reason: Safety, amenity and protection of public infrastructure and the environment.)

34. **COUNCIL PERMITS – FOR ALL ACTIVITIES ON COUNCIL LAND (CC)**

Works Permit

(as per Section 68 of the Local Government Act 1993 and Section 138 and 139 of the Roads Act 1993)

A Works Permit is required for construction of a vehicular crossing (driveway), new stormwater down pipe connection to kerb and gutter, new footpath and/or stormwater connection. A Works Permit Application Form is available from Council's Customer Centre

or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Standing Plant Permit

This permit must be applied for where it is intended to park a concrete pump, crane or other plant on the roadway or footpath. A Standing Plant Permit Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Skip Bin Permit

This permit must be applied for if you intend to place a skip bin on the roadway or footpath. A Skip Bin Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Temporary Full or Part Road Closure Permit

This permit must be applied for if you require a full or a part road closure to take place to assist in your construction works. Please use the Works Permit Application Form, which is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Hoarding Permit

This permit must be applied for if you intend to erect a Class A (fence type) or Class B (overhead type) hoarding along the street frontage(s). A Hoarding Permit Application Form is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Work Zone Permit

This permit must be applied for if you require permanent parking along the kerbside at the front of the site during construction works. A Work Zone Permit Application Form is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Ground Anchoring Permit

This permit must be applied for, for the installation of ground anchors under Council's footway/road reserve. It does not cover ground anchors under private properties. A separate approval is required to be obtained from Roads and Maritime Services (RMS) if it is proposed to install ground anchors under a State or Classified Regional Road (please refer to the end of this application form for more information).

(Reason: Council requirement)

35. **DILAPIDATION REPORT - PRE-COMMENCEMENT (CC)**

Subject to access being granted, a pre-commencement Dilapidation Report is to be undertaken on all adjoining properties, which in the opinion of a suitably qualified engineer, could be potentially affected by the construction of the project. The Dilapidation Report shall be carried out prior to the issue of a Construction Certificate.

The Dilapidation Report is to be prepared by a suitably Qualified Engineer with current Corporate Membership with the Institution of Engineers, Australia or Geotechnical Practitioner. The report shall include a photographic survey of adjoining properties detailing the physical condition of those properties, both internally and externally, including walls, ceilings, roof, structural members and other such items.

If access for undertaking the dilapidation survey is denied by an adjoining owner, the applicant must demonstrate, in writing, to Council's satisfaction attempts have been made to obtain access and/or advise the affected property owner of the reason for the survey and these attempts have been unsuccessful. Written concurrence must be obtained from Council in such circumstances.

The Report shall cover structural and geotechnical factors likely to arise from the development. A copy of this Report shall be submitted to Council as a record. The person having the benefit of the development consent must, at their own cost, rectify any damage caused to other properties during the construction of the project.

(Reason: To ensure no damage to adjoining properties occurs.)

36. EROSION AND SEDIMENTATION CONTROL PLAN (CC)

An Erosion and Sediment Control Plan is to be prepared where construction or excavation activity requires the disturbance of the soil surface and existing vegetation. Details including drawings and specifications must provide adequate measures for erosion and sediment control to ensure:

- i) Compliance with the approved Soil and Water Management Plan.
- ii) Removal or disturbance of vegetation and top soil is confined to within 3m of the approved building area (no trees to be removed without approval).
- iii) All uncontaminated run-off is diverted around cleared or disturbed areas.
- iv) Silt fences or other devices are installed to prevent sediment and other debris escaping from the cleared or disturbed areas into drainage systems or waterways.
- v) All erosion and sediment controls are fully maintained for the duration of demolition/development works.
- vi) Controls are put into place to prevent tracking of sediment by vehicles onto adjoining roadways.
- vii) All disturbed areas are rendered erosion-resistant by turfing, mulching, paving or similar.
- viii) All water pumped or otherwise removed from excavations or basement areas is filtered to achieve suspended solids/non filterable residue levels complying with the Australian Water Quality guidelines for Fresh and Marine Waters.
- ix) Pumped or overland flows of water are discharged so as not to cause, permit or allow erosion before the commencement of work (and until issue of the occupation certificate).

Details of the proposed soil erosion and sedimentation controls are to be submitted to the Principal Certifying Authority with the Construction Certificate Application. Under no circumstances are any works to commence, prior to these details being approved by the Principal Certifying Authority and the controls being in place on the site.

(Reason: Environmental protection.)

37. EXCAVATION - AFFECTING ADJOINING LAND (CC)

If an excavation associated with the approved development extends below the level of the base of the footings of a building on an adjoining allotment of land, the person having the benefit of the development consent must, at the person's own expense, comply with the requirements of clause 98E of the Environmental Planning and Assessment Regulation 2000, including:

- i) protect and support the adjoining premises from possible damage from the excavation, and

- ii) where necessary, underpin the adjoining premises to prevent any such damage.

The condition referred to in subclause (i) does not apply if the person having the benefit of the development consent owns the adjoining land or the owner of the adjoining land has given consent in writing to that condition not applying. Details shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Structural safety.)

38. FIRE SAFETY SCHEDULE (CC)

A Fire Safety Schedule specifying the fire safety measures (both current and proposed) which should be implemented in the building premises must be submitted with the Construction Certificate application, in accordance with Part 9 of Clause 168 of the Environmental Planning and Assessment Regulation 2000.

Note: A Construction Certificate cannot be issued until a Fire Safety Schedule is received.

(Reason: Compliance with the Environmental Planning and Assessment Act 1979.)

39. LANDSCAPING - LANDSCAPE PLAN REQUIRED (CC)

An amended landscape plan prepared by a qualified landscape architect or landscape consultant to a scale of 1:100 or 1:200, conforming to all relevant conditions of consent is to be submitted to the satisfaction of the Principal Certifying Authority with the Construction Certificate application.

The plan must include the following information:

- i) details demonstrating compliance with SDCDP 2005 in relation to landscaping requirements;
- ii) location of all existing and proposed landscape features including materials to be used;
- iii) all trees to be retained, removed or transplanted;
- iv) existing and proposed finished ground levels;
- v) top and bottom wall levels for both existing and proposed retaining and free standing walls; and
- vi) a detailed plant schedule which includes proposed species listed by botanical (genus and species) and common names, quantities of each species, pot sizes and the estimated size at maturity. A minimum of 25% of species shall be locally sourced indigenous species. Species shall be predominantly selected from Council's Recommended Tree List.

Consideration within the design should be given to the scale of planting in proportion to the proposed development, consistency with the existing landscape character of the area, potential views, solar access and privacy for neighbouring development.

(Reason: Landscape quality.)

40. LANDSCAPING - MAINTENANCE STRATEGY (CC)

To ensure the survival of landscaping following works, a landscape maintenance strategy for the owner/occupier to administer over a 12 month establishment period following the issue of the Occupation Certificate shall be prepared and provided to the satisfaction of the Principal Certifying Authority with the Construction Certificate application. The strategy is to address maintenance issues such as, but not limited to plant survival, irrigation, soil testing,

weeding, staking, fertilizing, remedial pruning and plant replacement.

(Reason: Ensure landscape survival.)

41. PRIVACY - OBSCURE GLAZING IN WET AREAS (CC)

All bathroom, ensuite and toilet windows shall be installed with obscure glazing. Plans shall be notated accordingly and details demonstrating compliance submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Privacy amenity.)

42. SECTION 94 CONTRIBUTION PAYMENT - DIRECT CONTRIBUTIONS PLAN (CC)

In accordance with the provisions of Section 94(1)(b) of the Environmental Planning and Assessment Act 1979 and the Strathfield Direct Development Contributions Plan 2010-2030, a contribution in the form of cash, cheque or credit card (financial transaction fee applies) shall be paid to Council for the following purposes:

Provision of Community Facilities	\$20,807.91
Provision of Major Open Space	\$94,669.77
Provision of Local Open Space	\$32,445.39
Provision Roads and traffic Management	\$7,641.18
Administration	\$1,794.22
TOTAL	\$157,358.46

The total amount of the contribution is valid as at the date of determination and is subject to quarterly indexation. Contributions shall be indexed at the time of payment in accordance with clause 2.14 of the Strathfield Direct Development Contributions Plan 2010-2030.

Contributions must be receipted by Council and submitted to the Accredited Certifier, prior to the issue of any Construction Certificate.

Please present a copy of this condition when paying the contribution at the Customer Service Centre so that it can be recalculated.

Note: A copy of Strathfield Council's Section 94 Direct Development Contributions Plan may be downloaded from Council's website.

(Reason: To enable the provision of public amenities and services required/anticipated as a consequence of increased demand resulting from the development.)

43. SECURITY PAYMENT - DAMAGE DEPOSIT FOR COUNCIL INFRASTRUCTURE (CC)

A security (damage deposit) of **\$15,000.00** (calculated in accordance with Council's adopted Fees and Charges) shall be paid to Council, prior to the issue of a Construction Certificate.

The deposit is required as security against any damage to Council property during works on the site. The applicant must bear the cost of all restoration works to Council's property damaged during the course of this development. All building work must be carried out in accordance with the Building Code of Australia.

Payment may be accepted in the form of cash, bank guarantee, cheque or credit card (financial transactions fees apply). Note: Additional fees apply for the lodgement of a bank guarantee in lieu of cash bond applies in accordance with Council's adopted Fees and

Charges.

Any costs associated with works necessary to be carried out to rectify any damages caused by the development, shall be deducted from the Damage Deposit.

Note: Should Council property adjoining the site be defective e.g. cracked footpath, broken kerb etc., this should be reported in writing, or by photographic record, submitted to Council at least seven (7) days prior to the commencement of any work on site. This documentation will be used to resolve any dispute over damage to infrastructure. It is in the applicant's interest for it to be as full and detailed as possible.

The damage deposit shall be refunded upon completion of all works upon receipt of a Final Occupation Certificate stage and inspection by Council.

(Reason: Protection of Council infrastructure.)

44. **TRAFFIC - CONSTRUCTION TRAFFIC MANAGEMENT PLAN (CC)**

A Construction Traffic Management Plan (CTMP) is to be prepared by an appropriately qualified Traffic Management Consultant and submitted to and approved by Council's Engineering Section, prior to the commencement of any works including demolition.

The following matters should be addressed in the CTMP (where applicable):

- i) description of the demolition, excavation and construction works;
- ii) site plan/s showing the site, roads, footpaths, site access points and vehicular movements;
- iii) size, type and estimated number of vehicular movements (including removal of excavated materials, delivery of materials and concrete to the site);
- iv) proposed route(s) from the arterial (state) road network to the site and the proposed route from the site back to the arterial road network;
- v) impacts of the work and vehicular movements on the road network, traffic and pedestrians and proposed methods to safely manage pedestrians and construction related vehicles in the frontage roadways;
- vi) any Traffic Control Plans (TCP's) proposed to regulate traffic and pedestrian movements for construction activities (such as concrete pours, crane installation/removal etc.);
- vii) proposed hours of construction related activities and vehicular movements to and from the site;
- viii) current/proposed approvals from other Agencies and Authorities (including Roads and Maritime Services, Police and State Transit Authority);
- ix) any activities proposed to be located or impact upon Council's road, footways or any public place;
- x) measures to maintain public safety and convenience;
- xi) any proposed road and/or footpath closures;
- xii) turning areas within the site for construction and spoil removal vehicles, allowing a forward egress for all construction vehicles on the site;
- xiii) locations of work zones (where it is not possible for loading/unloading to occur on the site) in the frontage roadways accompanied by supporting documentation that such work zones have been approved by the Local Traffic Committee and Council;
- xiv) location of any proposed crane and concrete pump and truck standing areas on and off the site (and relevant approvals from Council for plant on road);
- xv) a dedicated unloading and loading point within the site for all construction vehicles, plant and deliveries;
- xvi) material, plant and spoil bin storage areas within the site, where all materials are to be dropped off and collected;

- xvii) on-site parking area for employees, tradespersons and construction vehicles as far as possible;
- xviii) proposed areas within the site to be used for the storage of excavated material, construction materials and waste and recycling containers during the construction period; and
- xix) how it is proposed to ensure that soil/excavated material is not transported onto surrounding footpaths and roadways.

(Reason: To mitigate traffic impacts on the surrounding area during the construction period.)

45. **TREE BONDS (CC)**

A tree bond of **\$33,000.00** (calculated in accordance with Council's adopted Fees and Charges) shall be paid to Council, prior to the issue of a Construction Certificate.

The deposit is required as security against any damage to existing trees to be retained on Council's road reserve, during works on the site. The applicant must bear the cost of all restoration works to Council's property damaged during the course of this development.

Payment may be accepted in the form of cash, bank guarantee, cheque or credit card (financial transactions fees apply). Note: Additional fees apply for the lodgement of a bank guarantee in lieu of cash bond applies in accordance with Council's adopted Fees and Charges.

(Reason: To ensure the protection of trees to be retained on Council's Road Reserve.)

46. **WASTE MANAGEMENT PLAN (CC)**

A Waste Management Plan (WMP) is to be provided in accordance with Part H of Strathfield Consolidated Development Control Plan 2005. All requirements of the approved Waste Management Plan must be implemented during demolition, construction and on-going use of the premises.

The WMP must identify the types of waste that will be generated and all proposals to re-use, recycle or dispose of the waste. The WMP is to be submitted to the Principal Certifying Authority, prior to issue of the Construction Certificate.

NOTE: The property must be inspected by a Council Waste Officer prior to the issue of an Occupation Certificate so as to ensure that the correct number of general waste and recycling bins are ordered from Strathfield Council.

(Reason: To ensure appropriate management of waste.)

47. **WATER SUSTAINABILITY – GENERALLY (CC)**

Water collected in the rainwater tank must comprise roof water only and not surface water. Water from the rainwater tank must only be used for following purposes and not for human consumption:

- i) toilet flushing;
- ii) clothes washing;
- iii) garden irrigation;
- iv) car washing and similar outdoor uses;
- v) filling swimming pools, spa pools and ornamental ponds; and
- vi) fire fighting.

(Reason: To promote sustainable water management practice.)

48. WATER HEATING SYSTEMS - LOCATION OF (CC)

Water heating systems shall be located so as not to be visible from public places and the ground level of adjoining properties. Details (type and location) of the water heaters shall be submitted to and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To maintain streetscape character.)

CONDITIONS TO BE SATISFIED PRIOR TO THE COMMENCEMENT OF WORKS (CW)

49. APPOINTMENT OF A PRINCIPAL CERTIFYING AUTHORITY (PCA) (CW)

No work shall commence in connection with this Development Consent until:

- i) A construction certificate for the building work has been issued by the consent authority or a Principal Certifying Authority.
- ii) The person having the benefit of the development consent has appointed a principal certifying authority for the building work, and notified the principal certifying authority that the person will carry out the building work as an owner/builder, if that is the case.
- iii) The principal certifying authority has, no later than 2 days before the building work commences:
 - notified the Council of his or her appointment, and
 - notified the person having the benefit of the development consent of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- iv) The person having the benefit of the development consent, if not carrying out the work as an owner-builder, has:
 - appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved;
 - notified the principal certifying authority of such appointment; and
 - unless that person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- v) The person having the benefit of the development consent has given at least 2 days notice to the Council of the person's intention to commence the erection of the building.

Note: If the principal certifying authority is the Council, the nomination will be subject to the payment of a fee for the service to cover the cost of undertaking all necessary inspections and the issue of the appropriate certificates.

Under the Environment Planning and Assessment (Quality of Construction) Act, 2003, a sign must be erected in a prominent position on the work site showing the name, address and telephone number of the principal certifying authority; the name of the principal contractor (if any) for the building work and a telephone number at which that person may be contacted outside working hours. That sign must also state that unauthorised entry is prohibited. The sign must not be removed until all work has been completed.

(Reason: Statutory requirement.)

50. NOTICE OF COMMENCEMENT (CW)

No work shall commence until the following details are submitted to Council:

- i) a Notice of Commencement (form will be attached with issue of a Construction Certificate or available from our website) within two (2) days of the date on which it is proposed to commence works associated with the Development Consent;
- ii) details of the appointment of a Principal Certifying Authority (either Council or another Principal Certifying Authority); and
- iii) details of the name, address and licence details of the Builder.

(Reason: Statutory requirement.)

CONDITIONS TO BE SATISFIED DURING DEMOLITION AND BUILDING WORKS (DW)

51. CONTAMINATED LAND UNEXPECTED FINDS (DW)

In the instance works cause the generation of odours or uncovering of unexpected contaminants works are to immediately cease, Council is to be notified and a suitably qualified environmental scientist appointed to further assess the site.

The contaminated land situation is to be evaluated by the supervising environmental consultant and an appropriate response determined in consultation with the applicant, which is agreed to by Strathfield Council's Environmental Services Manager.

Note: Council may also request that a NSW EPA accredited site auditor is involved to assist with the assessment of the contaminated land situation and review any new contamination information. The applicant must also adhere to any additional conditions which may be imposed by the accredited site auditor.

(Reason: To ensure compliance with statutory requirements.)

52. FILL MATERIAL (DW)

The only waste derived material which may be received at the development site is:

- i) Virgin excavated material (within the meaning of the Protection of the Environment Operations Act 1997), and
- ii) any other waste-derived material the subject of a resource recovery exemption under cl.51A of the Protection of the Environment Operations (Waste) Regulation 2005 that is permitted to be used as fill material.

Any (b)-type material received at the development site must be accompanied by documentation certifying by an appropriately qualified environmental consultant the materials compliance with the exemption conditions; and this documentation must be provided to the Principal Certifying Authority on request.

(Reason: To ensure imported fill is of an acceptable standard for environmental protection purposes.)

53. OBSTRUCTION OF PUBLIC WAY NOT PERMITTED DURING WORKS (DW)

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances, without the prior approval of Council.

(Reason: To maintain public access and safety.)

54. PUBLIC INFRASTRUCTURE AND SERVICES (DW)

The applicant must comply with the requirements (including financial costs) of any relevant utility provider (e.g. Energy Australia, Sydney Water, Telstra, RMS, Council etc.) in relation to any connections, works, repairs, relocation, replacements and/or adjustments to public infrastructure or services affected by the development.

(Reason: To maintain public infrastructure and/or services.)

55. SITE REQUIREMENTS DURING DEMOLITION AND CONSTRUCTION

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standards AS 2601-2001.
- ii) Demolition must be carried out by a registered demolition contractor.
- iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out with close boarded, hardwood timber footpath protection pads. The pad shall cover the entire width of the footpath opening for the full width of the fence.
- iv) No blasting is to be carried out at any time during construction of the building.
- v) Care must be taken during demolition/ excavation/ building/ construction to prevent any damage to adjoining buildings.
- vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
- vii) Any demolition and excess construction materials are to be recycled wherever practicable.
- viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
- ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997.
- x) All excavated material should be removed from the site in the approved manner and be disposed of lawfully to a tip or other authorised disposal area.
- xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
- xii) All materials on site or being delivered to the site are to generally be contained within the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.
- xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts etc.) should be kept on site as evidence of approved methods of disposal and recycling.
- xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
- xv) Public footways and roadways adjacent to the site must be fully maintained and cleared of obstructions during construction unless prior separate approval from Council is obtained including payment of relevant fees.
- xvi) Building operations such as brick cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
- xvii) All site waters during excavation and construction must be contained on site in an

approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.

- xviii) Stamped plans, specifications, documentation and the consent shall be available on site at all times during construction.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

56. SURVEY REPORT OF APPROVED LEVELS DURING AND POST CONSTRUCTION (DW)

A Survey Certificate to Australian Height Datum shall be prepared by a Registered Surveyor as follows:

- i) At the completion of the first structural floor level prior to the pouring of concrete indicating the level of that floor and the relationship of the building to the boundaries.
- ii) At the completed height of the building, prior to the placement of concrete form work, or the laying of roofing materials.
- iii) At the completion of the development.

Progress certificates in response to points (1) through to (3) shall be provided to the Principal Certifying Authority at the time of carrying out relevant progress inspections. Under no circumstances is work allowed to proceed until such survey information is submitted to and approved by the Principal Certifying Authority.

(Reason: To ensure compliance with the approved plans.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE (OC)

57. DRAINAGE SYSTEM - MAINTENANCE OF EXISTING SYSTEM (OC)

Where elements of the existing drainage system are to be utilised, the existing drainage system shall be overhauled and maintained clear of silt and accumulated debris. Silt and the like shall be removed, not flushed from the system.

A certificate shall be provided by a suitably qualified person (a registered plumber or a person of equivalent or greater experience or qualification) to the satisfaction of the Principal Certifying Authority, prior to the issue of any Occupation Certificate to confirm that the system is in good working order and adequate to accept additional flows having regard to any relevant standards and/or Sydney Water requirements.

(Reason: Maintenance and environment.)

58. ENGINEERING WORKS (CERTIFICATION OF)

Prior to occupation of the premises, a Work As Executed (WAE) Plan of all engineering and/or drainage works is to be submitted to the Principal Certifying Authority. The WAE Plan is to be certified by a suitably Qualified Engineer, with Corporate Membership standing in the Institution of Engineers Australia and registered on the National Professional Engineers Register (NPER) under the appropriate professional category, demonstrating that:

- i) the stormwater drainage system; and/or
- ii) the car parking arrangement and area; and/or
- iii) any related footpath crossing works; and/or

- iv) the proposed basement pump and well system; and/or
- v) the proposed driveway and layback; and/or
- vi) any other civil works

have been constructed in accordance with the approved plans and any relevant Standards and Council policies/specifications.

For major works, such as subdivisions, works within the road reserve (requiring separate S138 approval) and as where specified by Council, a Part 4A Certificate will be required. It is strongly recommended that an Engineer supervise all engineering related works.

Where Council is not the Principal Certifying Authority, an electronic copy of the above documents is to be provided to Council, prior to the issue of any Occupation Certificate.

(Reason: Asset management.)

59. **FIRE SAFETY CERTIFICATION (OC)**

A fire safety certificate shall be obtained in accordance with Part 9, Division 4 of the Environmental Planning and Assessment Regulation 2000, prior to the issue of any Occupation Certificate.

An fire safety certificate is a certificate issued by the owner of a building to the effect that each essential fire safety measure specified in the current fire safety schedule for the part of the building to which the certificate relates:

- i) has been assessed by a properly qualified person; and
- ii) was found, when it was assessed, to be capable of performing to at least the standard required by the current fire safety schedule for the building for which the certificate is issued.

An interim fire safety certificate must be provided before an interim occupation certificate can be used for a building under Clause 153(2) of the Environmental Planning & Assessment Regulation 2000.

A final fire safety certificate must be provided before an interim occupation certificate can be used for a building under Clause 153(1) of the Environmental Planning & Assessment Regulation 2000.

A copy of the fire safety certificate and fire safety schedule shall be:

- i) submitted to Strathfield Council;
- ii) submitted to the Commissioner of the New South Wales Fire Brigade; and
- iii) prominently displayed in the building.

(Reason: Fire safety and statutory requirement.)

60. **LANDSCAPING - ARBORIST'S FOLLOW UP REPORT OF TREE/S TO BE RETAINED (OC)**

As part of the on-going assessment of the tree/s to be retained, the consulting arborist engaged by the applicant is to assess their health and any impacts suffered by them as a result of the proposed approved development, prior to the issue of an Occupation Certificate. Findings are to be compiled in a detailed report and submitted to the Principle Certifying Authority, which documents the following:

- i) methods of excavation or construction used to carry out the works;

- ii) any damage sustained by the tree/s as a result of the works;
- iii) any subsequent remedial works required to be carried out by the consulting arborist as a result of the damage; and
- iv) any future or on-going remedial work required to be carried out to ensure the long term retention of the tree/s.

(Reason: To ensure the survival of trees to be retained.)

61. OCCUPATION OF BUILDING (OC)

A person must not commence occupation or use (or change of use where an existing building) of the whole or any part of a new building (within the meaning of section 109H (4) of the Act) unless an Interim Occupation Certificate or Final Occupation Certificate has been issued in relation to the building or part.

The Principal Certifying Authority is required to be satisfied, amongst other things, that:

- i) all required inspections (including each applicable mandatory critical stage inspection) have been carried out; and
- ii) any preconditions to the issue of the certificate required by a development consent have been met.

Note: New building includes an altered portion of, or an extension to, an existing building.

(Reason: Statutory requirement.)

62. WORKS WITHIN THE ROAD RESERVE (CC)

Detailed drawings including long and short sections and specifications of all works within existing roads (including but not limited to structures, road works, driveway crossings, footpaths and stormwater drainage) shall be submitted to and approved by Council under Section 138 of the Roads Act 1993 and all fees and charges paid, prior to the issue of a Construction Certificate.

Detailed drawings and specifications are to be prepared and certified by an appropriately qualified Civil Engineer.

Upon completion of the works, the Applicant is to provide to Council with electronic copies of 'Work as Executed Plans'. The plans are to show relevant dimensions and finished levels and are to be certified by a surveyor.

The Applicant is to provide to Council, in an approved format, details of all public infrastructure created as part of the works.

All civil engineering works adjacent/near/outside 72-73 The Crescent, Homebush are to be fully supervised by Council. A maintenance period of six (6) months shall apply to the work, after it has been completed and approved. In that period the Applicant shall be liable for any part of the work which fails to perform in the manner outlined in Council's specifications, or as would reasonably be expected under the design conditions.

(Reason: To ensure compliance of engineering works/Council assets are constructed to acceptable standards for engineering works.)

63. STORMWATER - CERTIFICATION OF THE CONSTRUCTED DRAINAGE SYSTEM (OC)

The constructed stormwater system shall be certified by a suitably qualified person, in

accordance with Council's Stormwater Management Code, prior to the issue of any Occupation Certificate.

(Reason: Adequate stormwater management.)

64. STORMWATER - COVENANT AND RESTRICTION AS TO USER FOR STORMWATER CONTROLLED SYSTEMS (OC)

Prior to the issue of any Occupation Certificate, the applicant shall register a Positive Covenant and a Restriction as to User under section 88E and or section 88B of the Conveyancing Act as appropriate in favour of Council, ensuring the ongoing retention, maintenance and operation of the stormwater facility (on-site detention).

The wording on the 88B Instrument is to make reference to the Council file where the Construction plans and the Work As Executed (as built), plans are held. Typical wording can be obtained from Council's Specification for the Management of Stormwater document.

(Reason: To ensure the on-site detention and/or pump system is maintained to an appropriate operational standard.)

CONDITIONS TO BE SATISFIED DURING ONGOING USE OF THE PREMISES (OU)

65. BOARDING HOUSES - OPERATIONAL PLAN OF MANAGEMENT (OU)

An Operational Plan of Management is to be formulated and submitted to Council for approval, prior to the issue of any Occupation Certificate.

The Plan of Management must include the minimum criteria as stipulated in Schedule 2 (Standards for Places of Shared Accommodation) of the Local Government (General) Regulation, 2005 under the Local Government Act 1993, the Public Health Act, 1991, Boarding Houses Act 2012 and Boarding Houses Regulation 2013.

The plan shall be dated and the name and signature of the author of the document shall be included. The Plan of Management shall be displayed in prominent locations within the premises and a copy of the Plan shall be provided to all residents of the boarding house. The on-site Caretaker shall be responsible for ensuring that the terms of the Plan are adhered to at all times.

This Operational Plan of Management must incorporate the following:

- i) All the measures to be implemented on the premises in terms of safety & security, amenity and health including but not limited to matters relating to curfews and after-hours access, bringing of visitors on to the site, drug and alcohol policy (including smoking), and use of communal areas etc.
- ii) All the responsibilities of the Caretaker/Manager.
- iii) An Incident Register to be maintained by the Caretaker. This Register must be produced upon demand by any Council officer or NSW Police Officer. The Register must contain a direction that all incidents of a criminal nature are to be reported to the Police immediately.
- iv) Prior to commencement of the boarding house use, a notification letter shall be forwarded to Council, the Police and neighbours providing contact details for the Caretaker/Manager so that any issues regarding the operation of the premises etc. can be addressed promptly. Evidence of this letter being forwarded as required in this condition shall be provided to the Principal Certifying Authority, prior to the issue of any Occupation Certificate and commencement of the use.

The Plan of Management referred to in this condition shall be reviewed by Council annually from the date of issue of an Occupation Certificate by the Principal Certifying Authority. The operator of the boarding house shall contact Council annually to carry out this review and the review shall include the Incident Register referred to in point (iii) above. Should amendments be made to the Plan of Management an updated version of same shall be provided to Council and the residents of the boarding house within one (1) month of the annual review being completed.

(Reason: To minimise the impact of the use on surrounding residences.)

66. **BOARDING HOUSE - ONGOING USE OF (OU)**

Ongoing operation of the approved use for the purpose of a boarding house shall comply with the following:

- i) Use of the premises shall remain consistent with the definition of 'boarding house' as defined under Strathfield Local Environmental Plan 2012 as a building that:
 - is wholly or partly let in lodgings, and
 - provides lodgers with a principal place of residence for 3 months or more, and
 - may have shared facilities, such as a communal living room, bathroom, kitchen or laundry, and
 - has rooms, some or all of which may have private kitchen and bathroom facilities, that accommodate one or more lodgers but does not include "backpackers" accommodation, a group home, a serviced apartment, seniors housing or hotel or motel accommodation.
- ii) Subdivision of the approved boarding house under strata or community title is prohibited.
- iii) The use and operation of the boarding house shall comply with all applicable legislation/regulation and standards, including:
 - Boarding Houses Act 2012;
 - Boarding Houses Regulation 2013;
 - Local Government Act 1993; and
 - Schedule 2 (Standards for Places of Shared Accommodation) of the Local Government (General) Regulation 2005.
- iv) **The Boarding house is required to be registered on a register administered by NSW Fair Trading.**
- v) The maximum number of persons accommodated in a bedroom, or in a cubicle of a dormitory, must not exceed the number determined by allowing a minimum floor area within the bedroom or cubicle in accordance with the relevant provisions under the Public Health Act 1991 for each person.
- vi) No speakers or music is permitted outdoors or in the communal areas

(Reason: To minimise the impact of the boarding house on surrounding residences.)

RESOLUTION

We recommend to the General Manager that this item be **DEFERRED** to permit the applicant to satisfy the General Manager or his delegate in relation to the following matters:

1. **Vehicular access, on-site carparking arrangements and vehicular manoeuvring on and off the site. This is also to include disabled carparking.**
2. **On-site facilities for bulky waste storage.**

The Panel notes for the assistance of the General Manager that proposed special condition

6 should be deleted from any future consent since it is contrary Section 79C(2)(c) of the Environmental Planning and Assessment Act 1979.

FOR: P.Stein, B.Kirk, V.Albin, P.Smith

AGAINST: Nil

**** End Minutes - Report No. 3****

TO: Strathfield Local Planning Panel Meeting - 1 March 2018
REPORT: SLPP – Report No. 4
SUBJECT: DA2017/187- 5 ELVA STREET, STRATHFIELD
LOT 4 DP 302827
DA NO. 2017/187

RECOMMENDATION

That Development Application No. 2017/187 for demolition of existing structures and construction of a three (3) storey boarding house with (25) lodger rooms and one (1) managers room with basement car parking at 5 Elva Street, Strathfield be **APPROVED**, subject to the following conditions:

SPECIAL CONDITIONS (SC)

1. SYDNEY WATER (SC)

The approved plans must be submitted to the Sydney Water Tap in™ online service to determine whether the development will affect any Sydney Water sewer or water main, stormwater drains and/or easement, and if further requirements need to be met.

The Sydney Water Tap in™ online self-service replaces our Quick Check Agents as of 30 November 2015.

The Tap in™ service provides 24/7 access to a range of services, including:

- building plan approvals
- connection and disconnection approvals
- diagrams
- trade waste approvals
- pressure information
- water meter installations
- pressure boosting and pump approvals
- changes to an existing service or asset, e.g. relocating or moving an asset.

Sydney Water's Tap in™ online service is available at:

<https://www.sydneywater.com.au/SW/plumbing-building-developing/building/sydney-water-tap-in/index.htm>

(Reason: to comply with Sydney Water requirements)

2. MATERIALS - EXTERNAL FINISHES (SC)

The dulux "peplum half" rendered wall colour proposed in the finishes schedule *Elevations & Sections Plan Da.05, Rev B* prepared by Bechara Chan & Associates, dated 30th Jan 2018, shall be changed to dulux "peplum full" so as to better suit the Churchill Avenue heritage streetscape. The remaining external materials, finishes and colours proposed are to be consistent with the schedule submitted and approved by Council with the development application.

(Reason: Ensure compatibility with Churchill Avenue Heritage Streetscape)

3. LAUNDRY FACILITIES (SC)

Each lodger room shall be equipped with laundry facilities which meet the relevant Australian Standards. Details demonstrating compliance with this requirement shall be prepared and submitted to a Principal Certifying Authority for approval **prior to the issue of a Construction Certificate.**

(Reason: Ensure residential amenity is maintained)

- 3A. The recommendations in the supplementary report from the Arborist received by Council on the 7 February 2018 in so far it concerns the retention of Tree 2 *Corymbia Citriodora* shall be followed and implemented.

(Reason: To protect and retain Tree 2)

GENERAL CONDITIONS (GC)

4. APPROVED PLANS AND REFERENCE DOCUMENTATION (GC)

The development, except where modified by a condition(s) of consent, is to be carried out in accordance with the following plans and reference documentation:

Plans affixed with Council's 'Development Consent' stamp relating to Development Consent No. 2017/187:

Drawing No.	Title/Description	Prepared by	Issue / Revision & Date	Date received by Council
DA.01	Site Plan & Demolition Plan	Bechara Chan and Associates	B	7 February 2018
DA.02	Basement & Ground Floor Plan	Bechara Chan and Associates	B	7 February 2018
DA.03	First & Second Floor Plans	Bechara Chan and Associates	B	7 February 2018
DA.04	Driveway Section Plan	Bechara Chan and Associates	A	15 December 2017
DA.05	Elevations & Section Plans & Finishes Schedule	Bechara Chan and Associates	B	7 February 2018
DA.06	Building Footprint Plan	Bechara Chan and Associates	B	7 February 2018
L-01	Landscape Plan	Sussan Zino Landscape Architect	B	15 December 2017
A7195-Cover	General Notes – Stormwater Plan	Alpha Engineering and Development	B	7 February 2018
A7195 – SW0	Sediment and Erosion Control Plan	Alpha Engineering and	B	7 February 2018

1		Development		
A71 95- SW0 2	Basement Drainage Plan	Alpha Engineering and Development	B	7 February 2018
A71 95- SW0 3	Ground Floor Drainage Plan	Alpha Engineering and Development	B	7 February 2018
A71 95- SW0 4	Stormwater Sections and Details	Alpha Engineering and Development	B	7 February 2018

Reference Documentation affixed with Council's 'Development Consent' stamp relating to Development Consent No. 2017/187:

Title / Description	Prepared by	Issue/Revision & Date	Date received by Council
Statement of Environmental Effects	Planning Ingenuity	3 October 2017	15 December 2017
Flood Impact Assessment Report	Alpha Engineering	Rev B	7 February 2018
Traffic Impact Assessment	APEX Engineers	January 2018	7 February 2018
Arboricultural Assessment and Tree Management Plan	Horticultural Management Services	29 January 2018	7 February 2018
Acoustic DA Assessment	Acouras Consultancy	15 October 2017	15 December 2017
National Construction Code 2016 Compliance Report	Building Certificates Australia	Issue 1.0	15 December 2017
Geotechnical Desktop Study Report	Eiaustralia	1 September 2017	15 December 2017
Heritage Impact Statement	Ruth Daniel	August 2017	15 December 2017
Plan of Management	Planning Ingenuity		15 December 2017
Social Impact Assessment	Planning Ingenuity		15 December 2017
Waste Management Plan	Gihad Bechara	23 March 2017	15 December 2017

In the event of any inconsistency, the conditions of this consent shall prevail.

(Reason: To ensure that the form of the development undertaken is in accordance with the determination of Council.)

5. BOARDING HOUSE - APPROVED USE (GC)

This approval is granted for the use of the land for the purposes of a Boarding House comprising a maximum of (25) Boarding Rooms (plus one Manager's Room). This includes five (5) double rooms (maximum 2 persons per room) and (20) single rooms (maximum 1 person per room).

All lodgers shall be required to reside on the premises for a minimum period of three (3) months in accordance with the definition of a Boarding House under the Strathfield Local Environmental Plan 2013.

The approved boarding house must operate within the definition of 'boarding house' under SLEP 2012. The approved boarding house cannot be strata or community title subdivided.

(Reason: To clarify the terms of the approval and to control the maximum number of lodgers living in the premises at any one time.)

6. **BUILDING HEIGHT - MAXIMUM RL TO BE COMPLIED WITH (GC)**

The height of the building measured from Australian Height Datum (AHD) must not exceed Relative Level (RL) 20.885mAHD to the ridge of the lift shaft and 20.085AHD to the remaining roof ridge of the building.

(Reason: To ensure the approved building height is complied with.)

7. **CONSTRUCTION HOURS (GC)**

No construction or any other work related activities shall be carried out on the site outside the hours of 7.00 am to 5.00 pm Mondays to Fridays and 8am to 1pm Saturdays.

No building activities are to be carried out at any time on a Sunday or public holiday.

Where the development involves the use of jackhammers/ rock breakers and the like or other heavy machinery, such equipment may only be used between the hours of 7.00 am - 5.00 pm Monday to Friday only.

(Reason: To maintain amenity to adjoining land owners.)

8. **CONSTRUCTION WITHIN BOUNDARIES (GC)**

The development including but not limited to footings, walls, roof barges and guttering must be constructed wholly within the boundary of the premises. No portion of the proposed structure shall encroach onto the adjoining properties. Gates must be installed so they do not open onto any footpath or adjoining land.

(Reason: Approved works are to be contained wholly within the subject site.)

9. **DEMOLITION – GENERALLY (GC)**

Alteration and demolition of the existing building is limited to that documented on the approved plans (by way of notation). No approval is given or implied for removal and/or rebuilding of any portion of the existing building which is not shown to be altered or demolished.

(Reason: To ensure compliance with the approved development.)

10. **DEMOLITION - SITE SAFETY FENCING (GC)**

Site fencing is to be erected to a minimum height of 1.8m complying with WorkCover Guidelines, to exclude public access to the site, prior to any demolition works occurring and maintained for the duration of the demolition works.

If applicable, a separate Hoarding Application for the erection of an A class (fence type) or B class (overhead type) hoarding along the street frontage(s) complying with WorkCover requirements must be obtained including:

payment to Council of a footpath occupancy fee based on the area of footpath to be occupied and Council's Schedule of Fees and Charges before the commencement of work; and provision of a Public Risk Insurance Policy with a minimum cover of \$10 million in relation to the occupation of and works within Council's road reserve, for the full duration of the proposed works, must be obtained with a copy provided to Council.

(Reasons: Statutory requirement and health and safety.)

11. **FENCING - FRONT FENCE HEIGHT (GC)**

The front and side fencing (including the building line to a secondary street frontage on a corner site) shall not exceed a height of 1m above natural ground level.

(Reason: To ensure a positive contribution to the streetscape in accordance with the Strathfield Consolidated DCP 2005.)

12. **LANDSCAPING -IRRIGATION OF COMMON AND PRIVATE LANDSCAPE AREAS (GC)**

All common and private landscape areas including all planters of new multi-unit, commercial, mixed-use and industrial development are to have full coverage by a fully automatic irrigation system. The design, materials and installation are to be in accordance with Sydney Water Codes and satisfy all relevant Australian Standards. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior occupation of the premises.

(Reason: To ensure appropriate landscape maintenance.)

13. **LANDSCAPING - TREES PERMITTED TO BE REMOVED (GC)**

The following listed trees are permitted to be removed to accommodate the proposed development:

Tree	Height/ Spread (m)	Location
1)Schleferra actinophylla	7x4	Subject site
3)Fraxinus sp.	2x2	Subject site
4)Thuja sp	8x4	Subject site
S)Morus alba	7x7	Subject site

All trees permitted to be removed by this consent shall be replaced by species selected from Council's Recommended Tree List.

Replacement trees shall be a minimum 50 litre container size. Trees are to conform to the NATSPEC guide and Guide for assessing the quality of and purchasing of landscape trees by Ross Clarke, 2003. Trees are to be true to type, healthy and

vigorous at time of delivery and planting, shall be pest and disease free, free from injury and wounds and self-supporting; and shall be maintained until maturity.

All trees are to be staked and tied with a minimum of three (3) hardwood stakes. Ties are to be hessian and fixed firmly to the stakes, one tie at half the height of the main stem, others as necessary to stabilise the plant.

Root deflection barriers having a minimum depth of 600mm are to be installed adjacent to all footpaths and driveways.

Soil conditioner/fertilizer/moisture retention additive/s are to be applied in accordance with manufacturer's recommendations, and mixed into the backfilling soil after planting tree/s.

A minimum 75mm depth of organic mulch shall be placed within an area 0.5m from the base of the tree.

Details demonstrating compliance shall be demonstrated to the Principal Certifying Authority, prior to the issue of any Occupation Certificate.

(Reason: To ensure appropriate planting back onto the site.)

14. **LANDSCAPING- TREE PRESERVATION (GC)**

All street trees and trees on private property that are protected under Council's controls, shall be retained except where Council's prior written consent has been obtained. The felling, lopping, topping, ringbarking, wilful destruction or removal of any tree/s unless in conformity with this approval or subsequent approval is prohibited.

All healthy trees and shrubs identified for retention on the approved drawings are to be suitably protected in accordance with Australian Standard AS4970- Protection of Trees on Development prior to the commencement of any works (including any demolition and excavation) and maintained for the duration of the works.

(Reason: To ensure the protection of trees to be retained on the site.)

15. **LANDSCAPING- LANDSCAPING- TREE PRESERVATION (GC)**

All street trees and trees on private property that are protected under Council's controls, shall be retained except where Council's prior written consent has been obtained. The felling, lopping, topping, ringbarking, wilful destruction or removal of any tree/s unless in conformity with this approval or subsequent approval is prohibited. This applies to the following trees

Species	Location
2)Corymbia citriodora	Subject site

and protected by the establishment of a **protection zone** (in accordance with Australian Standard AS4970-*Protection of trees on development sites*) before any site works begin (including any demolition/excavation). The protection zone shall be maintained for the duration of works and implemented as follows:

- (a) A minimum 1.8m high barrier (Chain wire mesh panels, plywood or wooden

paling fence panels: refer to *AS4687-Temporary fencing and hoardings* for fencing requirements) shall be erected around the perimeter of the stated Protection Zone as measured from the base of the tree (or where practical). Shade cloth or similar should be attached to reduce the transport of dust, other particulate matter and liquids into the protected area. Fence posts and supports should have a diameter greater than 20mm and be located clear of roots. The barrier shall be constructed so as to prevent pedestrian and vehicular entry into the protection zone. The barrier shall not project beyond the kerb onto the roadway or any adjacent footpath.

(b) Signs identifying the Protection Zone should be installed on the fencing and be visible from within the development site. Lettering should comply with *AS4970-2009: Protection of Trees on Development Sites*.

(c) No concrete slurry or wash, building materials, builders' rubble, excavation soil or similar shall be placed or stored within the tree protection zone.

(d) The whole of the tree protection zone shall be mulched to a minimum depth of 75mm.

(e) The tree protection zone shall be regularly watered.

(f) Any major structural roots which are encountered shall be pruned by a qualified Arborist.

(g) **No excavation or construction shall be carried out** within the stated *Structural Root Zone* distances from the base of the trunk surface.

(h) Only permeable surfaces (e.g. decomposed granite, gravel, turfpave, permeable paving systems or soft landscaping) are permitted within the canopy spread of the trees to be protected.

All healthy trees and shrubs identified for retention on the approved drawings are to be suitably protected in accordance with Australian Standard AS4970 – Protection of Trees on Development prior to the commencement of any works (including any demolition and excavation) and maintained for the duration of the works.

Manual excavation is required within the canopy spread of the retained trees referred to in table above.

(Reason: To ensure tree preservation.)

16. LIGHTING (GC)

Any lighting of the premises shall be installed and maintained in accordance with Australian Standard AS 4282-1997: Control of the Obtrusive Effects of Outdoor Lighting so as to avoid annoyance to the occupants of adjoining premises or glare to motorists on nearby roads.

No flashing, moving or intermittent lighting, visible from any public place may be installed on the premises or external signage associated with the development, without the prior approval of Council.

(Reason: To protect the amenity of surrounding development and protect public safety.)

17. PRINCIPAL CERTIFYING AUTHORITY (PCA) IDENTIFICATION SIGN (GC)

Prior to commencement of any work, signage must be erected in a prominent position on the work site identifying:

- i) the Principal Certifying Authority (PCA) by showing the name, address and telephone number of the PCA;
- ii) the Principal Contractor by showing the Principal Contractor's name, address and telephone number (outside of work hours) for that person; and
- iii) the sign must state that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the work is being carried out, but must be removed when the work has been completed.

This clause does not apply to building work, subdivision work or demolition work that is carried out inside an existing building that does not affect the external walls of the building.

(Reason: Statutory requirement.)

18. PRIVACY - SCREEN PLANTING TO SIDE AND REAR BOUNDARIES (GC)

Evergreen shrubs with a minimum 5 litre container size achieving a minimum mature height of 3m shall be planted along the side and rear boundaries to provide suitable privacy screening. Screen planting shall be maintained at all times. Details of the selected plants shall be submitted to and approved by the Principal Certifying Authority. Compliance with this condition shall be certified by the Principal Certifying Authority, prior to occupation of the premises.

(Reason: To maintain privacy amenity to neighbouring residences.)

19. SITE MANAGEMENT (DURING DEMOLITION AND CONSTRUCTION WORKS)

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standard AS 2601-2001.
 - ii) Demolition must be carried out by a registered demolition contractor.
 - iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out.
 - iv) No blasting is to be carried out at any time during construction of the building.
 - v) Care must be taken during demolition/ excavation/ building/ construction to prevent any damage to adjoining buildings.
 - vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
 - vii) Any demolition and excess construction materials are to be recycled wherever practicable.
 - viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
 - ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997. All excavated material should be removed from the site in an approved manner and be disposed of lawfully to a tip or other authorised disposal area.
 - x) All waste must be contained entirely within the site.
 - xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
-

- xii) All materials on site or being delivered to the site are to generally be contained within the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.
- xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts, etc.) should be kept on site as evidence of approved methods of disposal or recycling.
- xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
- xv) Public footways, include nature strips and roadways adjacent to the site must be maintained and cleared of obstructions during construction. No building materials, waste containers or skips may be stored on the road reserve or footpath without prior separate approval from Council, including payment of relevant fees.
- xvi) Building operations such as brick-cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
- xvii) All site waters during excavation and construction must be contained on site in an approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.
- xviii) Any work must not prohibit or divert any natural overland flow of water.
- xix) Toilet facilities for employees must be provided in accordance with WorkCover NSW.
- xx) Protection pads are to be installed to the kerb and gutter where trucks and vehicles enter the site.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

20. **STORMWATER MANAGEMENT PLAN - CERTIFICATION REQUIREMENT (GC)**

A detailed Stormwater Management Plan (SWMP) in line with Council's Stormwater Management Code is to be prepared and certified by a practicing Chartered Professional Engineer on the National Professional Engineer's Register (NPER) at Engineers Australia and submitted to the Principal Certifying Authority and Council, prior to the issue of a Construction Certificate. The SWMP is to be based on the approved development as modified by any conditions of consent.

(Reason: To ensure appropriate provision is made for the disposal and management of stormwater generated by the development, and to ensure public infrastructure in Council's care and control is not overloaded.)

21. **SYDNEY WATER - STAMPED PLANS PRIOR TO COMMENCEMENT (GC)**

The approved plans must be submitted to a Sydney Water Quick Check agent or Customer Centre to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Plans will be appropriately stamped.

For Quick Check agent details please refer to the web site www.sydneywater.com.au (see Building Developing and Plumbing then Quick Check) or telephone 13 20 92. The consent authority or a Certifying Authority must ensure that a Quick Check agent/Sydney Water has stamped the plans before the commencement of work.

(Reason: Compliance with Sydney Water requirements.)

22. UTILITIES AND SERVICES - PROTECTION OF (GC)

Any footings or excavation to be located or undertaken adjacent to Council's stormwater must be designed to address the following requirements:

- i) all footings and excavation must be located wholly within the site and clear of any easement boundaries;
- ii) all footings and excavation must be located a minimum of 1000mm from the centreline of the pipeline or 500mm from the outside of the pipeline, whichever is the greater distance from the centreline; and
- iii) footings must extend to at least the depth of the invert of the pipeline unless the footings are to be placed on competent bedrock.

If permanent excavation is proposed beneath the obvert of the pipeline, suitable means to protect the excavation and proposed retaining structures from seepage or other water flow from the pipeline and surrounding subsoil, must be provided. The design must be prepared by a qualified practicing Structural/Civil Engineer.

Construction plans must be approved by the appropriate utility's office (e.g. council, Sydney Water Corporation) to demonstrate that the development complies with the utility's requirements.

The applicant must provide written evidence (e.g. compliance certificate, formal advice) of compliance with the requirements of all relevant utility providers (e.g. Water, Energy, Telecommunications, Gas).

(Reason: To ensure protection of Council assets.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A CONSTRUCTION CERTIFICATE (CC)**23. ACCESS - ACCESS FOR PEOPLE WITH DISABILITIES (CC)**

Access for people with disabilities must be provided in accordance with the requirements of the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

24. ACCESS - DISABLED TOILETS (CC)

Plans and details of the disabled toilet/s complying with the relevant Australian Standards, the Building Code of Australia, and with regard to the Disability Discrimination Act 1992. Plans shall be notated demonstrating compliance and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

Note: Disability (Access to Premises - Buildings) Standards 2010 - As of 1 May 2011, if access is provided to the extent covered by this Standard, then such access cannot be viewed as unlawful under the Disability Discrimination Act 1992.

(Reason: To provide equitable access for people(s) with disabilities in accordance with the relevant legislation and Australian Standards.)

25. BICYCLE STORAGE PROVISION (CC)

On-site provision for bicycle storage facilities shall be in accordance with the Strathfield Consolidated Development Control Plan 2005. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Compliance with SDCDP 2005 and to encourage sustainable transport options.)

26. BOARDING HOUSE - CONSTRUCTION OF (CC)

The construction of the boarding house shall comply with all applicable legislation/regulation and standards, including:

- i) Boarding Houses Act 2012;
- ii) Boarding Houses Regulation 2013;
- iii) Local Government Act 1993; and
- iv) Local Government Regulation 2005.

Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior to occupation of the premises.

(Reason: To ensure compliance with relevant legislation.)

27. BUILDING CODE OF AUSTRALIA - COMPLIANCE WITH (CC)

All architectural drawings, specifications and related documentation shall comply with the Building Code of Australia (BCA). All work must be carried out in accordance with the requirements of the Building Code of Australia (BCA).

In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of that Act, such a contract of insurance is to be in force before any building work authorised to be carried out by the consent commences.

Details demonstrating compliance with this condition are to be submitted to the Principle Certifying Authority, prior to issue of the Construction Certificate.

(Reason: This is a 'prescribed' condition under clause 98(1) of the Environmental Planning and Assessment Regulation 2000.)

28. CAR PARKING - BASEMENT CAR PARKING REQUIREMENTS (CC)

Details demonstrating compliance with the following is to be submitted to the Principal Certifying Authority, prior to issue of the Construction Certificate:

- i) Minimal internal clearance of the basement is 2.2m in accordance with BCA requirements.
 - ii) Driveways shall comply with Australian/New Zealand Standard AS/NZS 2890.1:2004 - Parking facilities - Off-street car parking and achieve a maximum gradient of 1:4.
 - iii) Basement entries and ramps/driveways within the property are to be no more than 3.5m wide.
-

- iv) Provision of pump-out systems and stormwater prevention shall be in accordance with Council's Stormwater Management Guide.

(Reason: To ensure suitable development.)

29. CAR PARKING - DISABLED CAR PARKING SPACES (CC)

One (1) of the car parking spaces provided as part of the total requirement shall be reserved for disabled persons. These spaces shall be a minimum of 2.4m wide x 5.4m long and located near pedestrian access routes designed for disabled persons. Each space shall be clearly marked as such. A shared area 2.4 m wide x 5.4m long shared area should be provided. Bollard shall be placed in this shared area.

Car parking for people with disabilities shall be provided in accordance with the Building Code of Australia, relevant Australian Standards and with regard to the Disability Discrimination Act 1992. Prior to the issue of a Construction Certificate, the plans shall be notated to demonstrate compliance.

The above details shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate.

(Reason: To ensure adequate parking for persons with a disability.)

30. CAR PARKING - VEHICULAR ACCESS RAMPS (CC)

Vehicular access ramps shall comply with the provisions of AS/NZS 2890.1:2004. Plans to be submitted shall contain the following details:

- i) Longitudinal section along the extreme wheel paths of each driveway/access ramp at a scale of 1:25 demonstrating compliance with the scraping provisions of AS/NZS 2890.1:2004. It shall include all levels and grades, including those levels stipulated as boundary levels, both existing and proposed. It shall extend from the centre-line of the roadway through to the parking area.
- ii) Sections showing the clearance to the underside of any overhead structure (minimum headroom requirements 2200mm minimum for standard headroom clearance or 2400mm where disabled access provisions are to be provided) demonstrating compliance with the provisions of AS/NZS 2890.1:2004.
- iii) Longitudinal section along the gutter line showing how it is intended to transition the vehicular crossing into the existing kerb and gutter. Boundary levels shall generally run parallel with the kerb levels.
- iv) Location of verge trees, street furniture and service installations.
- v) Superimposition of vehicle turning circles for access into parking spaces.
- vi) Certification that the design complies with AS/NZS 2890.1:2004 by a Qualified Engineer.

The certification referred to in (vi) above shall be submitted to the Principal Certifying Authority prior to the issue of a Construction Certificate (for the design) and to the Principal Certifying Authority prior to the issue of any Occupation Certificate for the 'as-built works'.

(Reason: To ensure adequate vehicular access can be achieved.)

31. CAR PARKING - COMPLIANCE WITH AS/NZS 2890.1:2004 (CC)

Car parking dimensions must comply with the Australian/New Zealand Standard AS/NZS 2890.1:2004 - Parking facilities - Off-street car parking. Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction

Certificate.

(Reason: To ensure compliance with Australian Standards relating to parking of vehicles.)

32. CAR PARKING - VEHICULAR CIRCULATION, AISLE AND RAMP WIDTHS (CC)

The aisle widths, internal circulation, ramp widths and grades of the car park shall comply with the Roads and Traffic Authority Guidelines and ASNZS 2890.1:2004 - Off-Street Car Parking Code.

Vehicular manoeuvring paths are to be prepared demonstrating that all vehicles can enter or depart the site in a forward direction without encroaching on required car parking spaces.

(Reason: To ensure compliance with Australian Standards relating to manoeuvring, access and parking of vehicles.)

33. CAR PARKING - VEHICULAR CROSSING WIDTH AT PROPERTY BOUNDARY (CC)

The internal driveway must be a minimum 5.50m wide (clear width) for the first 6 metres inside the property so as to allow entering & exiting vehicles to pass within the site. Should the driveway narrow after this point it is then to be designed with a minimum 1.5m x 1.5m splay to allow the passing to work. Details demonstrating compliance shall be submitted to the Principal Certifying Authority, prior the issue of a Construction Certificate.

(Reason: Safety and traffic management)

34. COMMENCEMENT OF WORKS (NO WORKS UNTIL A CC IS OBTAINED)

Building work, demolition or excavation must not be carried out until a Construction Certificate has been issued by either Strathfield Council or a Principal Certifying Authority.

Demolition of any part of a building triggers 'commencement of erection of building' pursuant of section 81A(2) of the EP&A Act 1979. Accordingly, demolition works must not commence until a Construction Certificate has been issued, a Principal Certifying Authority has been appointed and a Notice of Commencement has been issued.

(Reason: To ensure compliance with statutory provisions.)

35. CONSTRUCTION AND ENVIRONMENTAL MANAGEMENT PLAN (CC)

The applicant must prepare and submit a Construction and Environmental Management Plan (CEMP) to the Principal Certifying Authority, including:

- i) Detailed information on any approvals required from other authorities prior to or during construction.
 - ii) Traffic management, including details of:
 - ingress and egress of vehicles to the site;
 - management of loading and unloading of materials;
 - the location of heavy vehicle parking off-site; and
 - designated routes for vehicles to the site.
 - iii) The proposed areas within the site to be used for a builder's site office and amenities, the storage of excavated material, construction materials and waste containers during the construction period.
 - iv) Erosion and sediment control, detailing measures and procedures consistent with
-

- the requirements of Council's guidelines for managing stormwater, including:
- the collection and treatment of stormwater and wastewater generated on site prior to discharge; and
 - procedures to prevent run-off of solid material and waste from the site.
- v) Waste management, including:
- details of the types and estimated volumes of waste materials that will be generated;
 - procedures for maximising reuse and recycling of construction materials; and
 - details of the off-site disposal or recycling facilities for construction waste.
- vi) Dust control, outlining measures to minimise the generation and off-site transmission of dust and fine particles, such as watering or damp cloth fences.
- vii) A soil and water management plan, which includes:
- measures to minimise the area of soils exposed at any one time and conserve top soil;
 - identification and protection of proposed stockpile locations;
 - preservation of existing vegetation and revegetation;
 - measures to prevent soil, sand, sediments leaving the site in an uncontrolled manner;
 - measures to control surface water flows through the site in a manner that diverts clean run-off around disturbed areas, minimises slope gradient and flow distance within disturbed areas, ensures surface run-off occurs at non-erodible velocities, and ensures disturbed areas are promptly rehabilitated;
 - details of sediment and erosion control measures in place before work commences;
 - measures to ensure materials are not tracked onto the road by vehicles entering or leaving the site; and
 - details of drainage to protect and drain the site during works.
- viii) Asbestos management procedures:
- Anyone who removes, repairs or disturbs bonded or a friable asbestos material must hold a current removal licence from Workcover NSW holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal License which ever applies and a current WorkCover Demolition License where works involve demolition. To find a licensed asbestos removalist please see www.workcover.nsw.gov.au
 - Removal of asbestos by a person who does not hold a Class A or Class B asbestos removal license is permitted if the asbestos being removed is 10m² or less of non-friable asbestos (approximately the size of a small bathroom). Friable asbestos materials must only be removed by a person who holds a current Class A asbestos license.
 - Before starting work, a work site-specific permit approving each asbestos project must be obtained from Workcover NSW. A permit will not be granted without a current Workcover licence. All removal, repair or disturbance of or to asbestos material must comply with the following:
 - The Work Health and Safety Act 2011;
 - The Work Health and Safety Regulation 2011;
 - How to Safety Remove Asbestos Code of Practice – WorkCover 2011; and
 - Safe Work Australia Code of Practice for the Management and Control of Asbestos in the Workplace.
 - Following completion of asbestos removal works undertaken by a licensed asbestos removalist re-occupation of a workplace must not occur until an independent and suitably licensed asbestos removalist undertakes a clearance inspection and issues a clearance certificate.
 - The developer or demolition contractor must notify adjoining residents at least two (2) working days (i.e. Monday to Friday exclusive of public holidays) prior to the commencement of asbestos removal works. Notification is to include, at a
-

minimum:

- the date and time when asbestos removal works will commence;
- the name, address and business hours contact telephone number of the demolisher, contractor and/or developer;
- the full name and license number of the asbestos removalist/s; and
- the telephone number of WorkCover's Hotline 13 10 50
- warning signs informing all people nearby that asbestos removal work is taking place in the area. Signs should be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs should be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs should be in accordance with AS 1319-1994 Safety signs for the occupational environment for size, illumination, location and maintenance; and
- appropriate barricades installed as appropriate to prevent public access and prevent the escape of asbestos fibres. Barricades must be installed prior to the commencement of asbestos removal works and remain in place until works are completed.

(Reason: Safety, amenity and protection of public infrastructure and the environment.)

36. **COUNCIL PERMITS – FOR ALL ACTIVITIES ON COUNCIL LAND (CC)**

Works Permit

(as per Section 68 of the Local Government Act 1993 and Section 138 and 139 of the Roads Act 1993)

A Works Permit is required for construction of a vehicular crossing (driveway), new stormwater down pipe connection to kerb and gutter, new footpath and/or stormwater connection. A Works Permit Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Standing Plant Permit

This permit must be applied for where it is intended to park a concrete pump, crane or other plant on the roadway or footpath. A Standing Plant Permit Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Skip Bin Permit

This permit must be applied for if you intend to place a skip bin on the roadway or footpath. A Skip Bin Application Form is available from Council's Customer Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Temporary Full or Part Road Closure Permit

This permit must be applied for if you require a full or a part road closure to take place to assist in your construction works. Please use the Works Permit Application Form, which is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website. Please note a Road Closure Permit is not required for standing plant.

Hoarding Permit

This permit must be applied for if you intend to erect a Class A (fence type) or Class B (overhead type) hoarding along the street frontage(s). A Hoarding Permit Application Form

is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Work Zone Permit

This permit must be applied for if you require permanent parking along the kerbside at the front of the site during construction works. A Work Zone Permit Application Form is available from Council's Customer Service Centre or can be downloaded from Council's website. The applicable fees and charges are located on Council's website.

Ground Anchoring Permit

This permit must be applied for, for the installation of ground anchors under Council's footway/road reserve. It does not cover ground anchors under private properties. A separate approval is required to be obtained from Roads and Maritime Services (RMS) if it is proposed to install ground anchors under a State or Classified Regional Road (please refer to the end of this application form for more information).

(Reason: Council requirement)

37. DILAPIDATION REPORT - PRE-COMMENCEMENT (CC)

Subject to access being granted, a pre-commencement Dilapidation Report is to be undertaken on all adjoining properties, which in the opinion of a suitably qualified engineer, could be potentially affected by the construction of the project. The Dilapidation Report shall be carried out prior to the issue of a Construction Certificate.

The Dilapidation Report is to be prepared by a suitably Qualified Engineer with current Corporate Membership with the Institution of Engineers, Australia or Geotechnical Practitioner. The report shall include a photographic survey of adjoining properties detailing the physical condition of those properties, both internally and externally, including walls, ceilings, roof, structural members and other such items.

If access for undertaking the dilapidation survey is denied by an adjoining owner, the applicant must demonstrate, in writing, to Council's satisfaction attempts have been made to obtain access and/or advise the affected property owner of the reason for the survey and these attempts have been unsuccessful. Written concurrence must be obtained from Council in such circumstances.

The Report shall cover structural and geotechnical factors likely to arise from the development. A copy of this Report shall be submitted to Council as a record. The person having the benefit of the development consent must, at their own cost, rectify any damage caused to other properties during the construction of the project.

(Reason: To ensure no damage to adjoining properties occurs.)

38. DRIVEWAY DESIGN - SPEED HUMP AND STOP SIGN ON EXIT (CC)

The applicant shall install a stop sign and a speed hump at the exit from the site. The stop sign must be accompanied by the associated line marking and the speed hump shall be set back by 1.5 metres from the boundary alignment. The devices shall be designed and constructed in accordance with the provision of all relevant Australian Standards. The building plans shall indicate compliance with this requirement, prior to the issue of a Construction Certificate.

(Reason: Traffic safety and management.)

39. EROSION AND SEDIMENTATION CONTROL PLAN (CC)

An Erosion and Sediment Control Plan is to be prepared where construction or excavation activity requires the disturbance of the soil surface and existing vegetation. Details including drawings and specifications must provide adequate measures for erosion and sediment control to ensure:

- i) Compliance with the approved Soil and Water Management Plan.
- ii) Removal or disturbance of vegetation and top soil is confined to within 3m of the approved building area (no trees to be removed without approval).
- iii) All uncontaminated run-off is diverted around cleared or disturbed areas.
- iv) Silt fences or other devices are installed to prevent sediment and other debris escaping from the cleared or disturbed areas into drainage systems or waterways.
- v) All erosion and sediment controls are fully maintained for the duration of demolition/development works.
- vi) Controls are put into place to prevent tracking of sediment by vehicles onto adjoining roadways.
- vii) All disturbed areas are rendered erosion-resistant by turfing, mulching, paving or similar.
- viii) All water pumped or otherwise removed from excavations or basement areas is filtered to achieve suspended solids/non filterable residue levels complying with the Australian Water Quality guidelines for Fresh and Marine Waters.
- ix) Pumped or overland flows of water are discharged so as not to cause, permit or allow erosion before the commencement of work (and until issue of the occupation certificate).

Details of the proposed soil erosion and sedimentation controls are to be submitted to the Principal Certifying Authority with the Construction Certificate Application. Under no circumstances are any works to commence, prior to these details being approved by the Principal Certifying Authority and the controls being in place on the site.

(Reason: Environmental protection.)

40. **EXCAVATION - AFFECTING ADJOINING LAND (CC)**

If an excavation associated with the approved development extends below the level of the base of the footings of a building on an adjoining allotment of land, the person having the benefit of the development consent must, at the person's own expense, comply with the requirements of clause 98E of the Environmental Planning and Assessment Regulation 2000, including:

- i) protect and support the adjoining premises from possible damage from the excavation, and
- ii) where necessary, underpin the adjoining premises to prevent any such damage.

The condition referred to in subclause (i) does not apply if the person having the benefit of the development consent owns the adjoining land or the owner of the adjoining land has given consent in writing to that condition not applying. Details shall be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Structural safety.)

41. **FIRE SAFETY SCHEDULE (CC)**

A Fire Safety Schedule specifying the fire safety measures (both current and proposed) which should be implemented in the building premises must be submitted with the Construction Certificate application, in accordance with Part 9 of Clause 168 of the Environmental Planning and Assessment Regulation 2000.

Note: A Construction Certificate cannot be issued until a Fire Safety Schedule is received.

(Reason: Compliance with the Environmental Planning and Assessment Act 1979.)

42. **FLOODING - COMPLY WITH FLOOD IMPACT REPORT (CC)**

The applicant shall comply with the flood recommendations provided in the Flood Impact Report prepared by Alpha Engineering. A certificate from a suitably qualified Engineer shall be submitted to the Certifying Authority stating compliance with these recommendations, prior to the issue of a Construction Certificate.

(Reason: To mitigate flood risk and associated damage.)

43. **LANDSCAPING - AMENDED LANDSCAPE PLAN REQUIRED (CC)**

Prior to the issue of a construction certificate the applicant shall submit and have approved by the Principal Certifying Authority (PCA) a detailed landscape implementation report certifying that landscaping has been installed in accordance with the proposed landscape plan with the landscape plan which is to be amended to include the retention of Tree 2 *Corymbia citriodora* and the Landscape provisions contained within section 10.0 of Part A of the Strathfield Council Development Control Plan. The plans shall include the following:

- (a) A minimum 1.5m wide garden is to be established to the full width of the property frontage (except for vehicular crossings and pedestrian ways). The garden bed is to be planted with suitable shrubs and ground cover plants;
- (b) A detailed planting schedule for all garden areas indicating the species type, height, number and size;
- (c) Soft landscaping shall account for no less than ***the approved FSR for the development on the site;***
- (d) Details of all hard and soft surfaces such as turf, gravel, paving, stepping stones and the like shall be shown;
- (e) Gardens should feature a mix of trees, shrubs, grasses and ground covers. A minimum of 25% of all plantings shall be locally indigenous species;
- (f) Evergreen shrubs with a minimum 5 litre container size achieving a minimum mature height of 3m shall be planted along side and rear boundaries to provide privacy screening; and
- (g) The plan shall demonstrate compliance with any other landscape condition of consent.

Should Council not act as the Certifying Authority a copy of the plan shall be forwarded to

Council as part of the Construction

Certificate.

(Reason: Landscape quality.)

44. **LANDSCAPING - MAINTENANCE STRATEGY (CC)**

To ensure the survival of landscaping following works, a landscape maintenance strategy for the owner/occupier to administer over a 12 month establishment period following the

issue of the Occupation Certificate shall be prepared and provided to the satisfaction of the Principal Certifying Authority with the Construction Certificate application. The strategy is to address maintenance issues such as, but not limited to plant survival, irrigation, soil testing, weeding, staking, fertilizing, remedial pruning and plant replacement.

(Reason: Ensure landscape survival.)

45. **LANDSCAPING ON SLAB (CC)**

To ensure the site landscaping thrives, the on slab landscaping shown on the approved landscaping plan is to be designed to include a minimum soil depth of 650mm for shrubs and trees; and 300mm for grass and ground covers. Adequate drainage provision and a permanent, automatic irrigation system conforming to Sydney Water requirements shall be included. Details demonstrating compliance shall be submitted to the Principal Certifying Authority with the Construction Certificate application.

(Reason: Ensure landscape survival.)

46. **PRIVACY - OBSCURE GLAZING IN WET AREAS (CC)**

All bathroom, ensuite and toilet windows shall be installed with obscure glazing. Plans shall be notated accordingly and details demonstrating compliance submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: Privacy amenity.)

47. **SECTION 94 CONTRIBUTION PAYMENT - DIRECT CONTRIBUTIONS PLAN (CC)**

In accordance with the provisions of Section 94(1)(b) of the Environmental Planning and Assessment Act 1979 and the Strathfield Direct Development Contributions Plan 2010-2030, a contribution in the form of cash, cheque or credit card (financial transaction fee applies) shall be paid to Council for the following purposes:

Provision of Community Facilities	\$37,679.42
Provision of Major Open Space	\$171,430.07
Provision of Local Open Space	\$58,752.82
Provision Roads and Traffic Management	\$12,893.42
Administration	<u>\$3249.00</u>
TOTAL	\$284,004.73

The total amount of the contribution is valid as at the date of determination and is subject to quarterly indexation. Contributions shall be indexed at the time of payment in accordance with clause 2.14 of the Strathfield Direct Development Contributions Plan 2010-2030.

Contributions must be receipted by Council and submitted to the Accredited Certifier, prior to the issue of any Construction Certificate.

Please present a copy of this condition when paying the contribution at the Customer Service Centre so that it can be recalculated.

Note: A copy of Strathfield Council's Section 94 Direct Development Contributions Plan may be downloaded from Council's website.

(Reason: To enable the provision of public amenities and services required/anticipated as a consequence of increased demand resulting from the development.)

48. SECURITY PAYMENT - DAMAGE DEPOSIT FOR COUNCIL INFRASTRUCTURE (CC)

A security (damage deposit) of **\$18,000.00** (calculated in accordance with Council's adopted Fees and Charges) shall be paid to Council, prior to the issue of a Construction Certificate.

The deposit is required as security against any damage to Council property during works on the site. The applicant must bear the cost of all restoration works to Council's property damaged during the course of this development. All building work must be carried out in accordance with the Building Code of Australia.

Payment may be accepted in the form of cash, bank guarantee, cheque or credit card (financial transactions fees apply). Note: Additional fees apply for the lodgement of a bank guarantee in lieu of cash bond applies in accordance with Council's adopted Fees and Charges.

Any costs associated with works necessary to be carried out to rectify any damages caused by the development, shall be deducted from the Damage Deposit.

Note: Should Council property adjoining the site be defective e.g. cracked footpath, broken kerb etc., this should be reported in writing, or by photographic record, submitted to Council at least seven (7) days prior to the commencement of any work on site. This documentation will be used to resolve any dispute over damage to infrastructure. It is in the applicant's interest for it to be as full and detailed as possible.

The damage deposit shall be refunded upon completion of all works upon receipt of a Final Occupation Certificate stage and inspection by Council.

(Reason: Protection of Council infrastructure.)

49. STORMWATER DRAINAGE (CC)

The following stormwater precautions are required to be provided on the site:

- i) Grated drains shall be provided along the basement entry at the vehicular crossing(s) and are to connect to the internal drainage system.
- ii) Overflow paths shall be provided to allow for flows in excess of the capacity of the pipe/drainage system draining the site.
- iii) Allowance shall be made for surface runoff from adjacent properties, and to retain existing surface flow path systems through the site. Any redirection or treatment of these flows shall not adversely affect any other properties
- iv) Boundary fencing shall be erected in such a manner as not to interfere with the natural flow of ground and surface water to the detriment of any other party.

(Reason: To ensure the site is drained appropriately and does not interfere with the natural flow of flood waters.)

50. TRAFFIC - CONSTRUCTION TRAFFIC MANAGEMENT PLAN (CC)

A Construction Traffic Management Plan (CTMP) is to be prepared by an appropriately qualified Traffic Management Consultant and submitted to and approved by Council's Engineering Section, prior to the commencement of any works including demolition.

The following matters should be addressed in the CTMP (where applicable):

- i) description of the demolition, excavation and construction works;
-

- ii) site plan/s showing the site, roads, footpaths, site access points and vehicular movements;
- iii) size, type and estimated number of vehicular movements (including removal of excavated materials, delivery of materials and concrete to the site);
- iv) proposed route(s) from the arterial (state) road network to the site and the proposed route from the site back to the arterial road network;
- v) impacts of the work and vehicular movements on the road network, traffic and pedestrians and proposed methods to safely manage pedestrians and construction related vehicles in the frontage roadways;
- vi) any Traffic Control Plans (TCP's) proposed to regulate traffic and pedestrian movements for construction activities (such as concrete pours, crane installation/removal etc.);
- vii) proposed hours of construction related activities and vehicular movements to and from the site;
- viii) current/proposed approvals from other Agencies and Authorities (including Roads and Maritime Services, Police and State Transit Authority);
- ix) any activities proposed to be located or impact upon Council's road, footways or any public place;
- x) measures to maintain public safety and convenience;
- xi) any proposed road and/or footpath closures;
- xii) turning areas within the site for construction and spoil removal vehicles, allowing a forward egress for all construction vehicles on the site;
- xiii) locations of work zones (where it is not possible for loading/unloading to occur on the site) in the frontage roadways accompanied by supporting documentation that such work zones have been approved by the Local Traffic Committee and Council;
- xiv) location of any proposed crane and concrete pump and truck standing areas on and off the site (and relevant approvals from Council for plant on road);
- xv) a dedicated unloading and loading point within the site for all construction vehicles, plant and deliveries;
- xvi) material, plant and spoil bin storage areas within the site, where all materials are to be dropped off and collected;
- xvii) on-site parking area for employees, tradespersons and construction vehicles as far as possible;
- xviii) proposed areas within the site to be used for the storage of excavated material, construction materials and waste and recycling containers during the construction period; and
- xix) how it is proposed to ensure that soil/excavated material is not transported onto surrounding footpaths and roadways.

(Reason: To mitigate traffic impacts on the surrounding area during the construction period.)

51. UTILITIES AND TELECOMMUNICATIONS - TELECOMMUNICATIONS ASSETS (CC)

Provision must be made for relocation of telecommunications network assets including underground placement of any existing aerial cables and infrastructure. Any costs associated with the relocation of the above are at the requestor's expense. Any disturbance to public land as a result of the undergrounding of services shall be restored at no cost to Council.

Details are to be submitted to the Principal Certifying Authority with the Construction Certificate application.

(Reason: To ensure suitable relocation of telecommunications infrastructure if required.)

52. VEHICULAR CROSSINGS - WORKS PERMIT FOR CONSTRUCTION OF (CC)

Full-width, heavy-duty concrete vehicular crossing(s) shall be provided across the footpath at the entrance(s) and/or exit(s) to the site and designed in accordance with Council's guidelines and specifications. In this regard, a Works Permit is to be obtained (available from Council's Customer Services Centre or downloaded from Council's website), and the appropriate fees and charges paid, prior to the lodgement of a Construction Certificate.

(Reason: To ensure appropriate access to the site can be achieved.)

53. VENTILATION SYSTEMS – MECHANICAL (CC)

The mechanical ventilation system is to comply with the following:

- i) The Building Code of Australia;
- ii) Protection of the Environment Operations Act 1997; and
- iii) Australian Standard AS1668-1991.

In addition, odour control measures, such as activated carbon or catalytic oxidisers, must be used to treat ventilation gases prior to discharge. The method of odour control must be designed by a suitably qualified mechanical ventilation engineer.

Details demonstrating compliance with the above are to be submitted to the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To ensure the mechanical ventilation system complies with the relevant requirements/standards.)

54. WASTE MANAGEMENT PLAN (CC)

A Waste Management Plan (WMP) is to be provided in accordance with Part H of Strathfield Consolidated Development Control Plan 2005. All requirements of the approved Waste Management Plan must be implemented during demolition, construction and on-going use of the premises.

The WMP must identify the types of waste that will be generated and all proposals to re-use, recycle or dispose of the waste. The WMP is to be submitted to the Principal Certifying Authority, prior to issue of the Construction Certificate.

NOTE: The property must be inspected by a Council Waste Officer prior to the issue of an Occupation Certificate so as to ensure that the correct number of general waste and recycling bins are ordered from Strathfield Council.

(Reason: To ensure appropriate management of waste.)

55. WATER SUSTAINABILITY - WATER SENSITIVE URBAN DESIGN (CC)

Details of the Water Sensitive Urban Design (WSUD) components (stormwater treatment measures) shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate. Details shall demonstrate compliance with the water conservation and stormwater quality targets set out under Sections 3.1 and 3.2 respectively under Part N of the SDCDP 2005, and be prepared by a suitably qualified professional engineer.

(Reason: To promote Water Sensitive Urban Design.)

56. WATER SUSTAINABILITY – GENERALLY (CC)

Water collected in the rainwater tank must comprise roof water only and not surface water. Water from the rainwater tank must only be used for following purposes and not for human consumption:

- i) toilet flushing;
- ii) clothes washing;
- iii) garden irrigation;
- iv) car washing and similar outdoor uses;
- v) filling swimming pools, spa pools and ornamental ponds; and
- vi) fire fighting.

(Reason: To promote sustainable water management practice.)

57. WATER HEATING SYSTEMS - LOCATION OF (CC)

Water heating systems shall be located so as not to be visible from public places and the ground level of adjoining properties. Details (type and location) of the water heaters shall be submitted to and approved by the Principal Certifying Authority, prior to the issue of a Construction Certificate.

(Reason: To maintain streetscape character.)

58. WORKS ZONE - APPROVAL BY COUNCIL'S TRAFFIC COMMITTEE (CC)

An application for a 'Works Zone' must be submitted to and approved by the Strathfield Council Traffic Committee prior to the commencement of any site work (including demolition).

The suitability of the proposed length and duration of the Works Zone is to be demonstrated in the application for the Works Zone. The application for the Works Zone must be submitted to Council at least six (6) weeks prior to the commencement of work on the site to allow for assessment and tabling of agenda for the Strathfield Council Traffic Committee.

The requirement for a Works Zone may be varied or waived only if it can be demonstrated in the Construction Traffic Management Plan (to the satisfaction of Council) that all construction related activities (including all loading and unloading operations) can and will be undertaken wholly within the site. The written approval of Council must be obtained to provide a Works Zone or to waive the requirement to provide a Works Zone prior to the commencement of any site work.

(Reason: Council requirement.)

CONDITIONS TO BE SATISFIED PRIOR TO THE COMMENCEMENT OF WORKS (CW)

59. APPOINTMENT OF A PRINCIPAL CERTIFYING AUTHORITY (PCA) (CW)

No work shall commence in connection with this Development Consent until:

- i) A construction certificate for the building work has been issued by the consent authority or a Principal Certifying Authority.
- ii) The person having the benefit of the development consent has appointed a principal certifying authority for the building work, and notified the principal certifying authority that the person will carry out the building work as an owner/builder, if that is the case.
- iii) The principal certifying authority has, no later than 2 days before the building work

commences:

- notified the Council of his or her appointment, and
 - notified the person having the benefit of the development consent of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- iv) The person having the benefit of the development consent, if not carrying out the work as an owner-builder, has:
- appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved;
 - notified the principal certifying authority of such appointment; and
 - unless that person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work.
- v) The person having the person having the benefit of the development consent has given at least 2 days notice to the Council of the person's intention to commence the erection of the building.

Note: If the principal certifying authority is the Council, the nomination will be subject to the payment of a fee for the service to cover the cost of undertaking all necessary inspections and the issue of the appropriate certificates.

Under the Environment Planning and Assessment (Quality of Construction) Act, 2003, a sign must be erected in a prominent position on the work site showing the name, address and telephone number of the principal certifying authority; the name of the principal contractor (if any) for the building work and a telephone number at which that person may be contacted outside working hours. That sign must also state that unauthorised entry is prohibited. The sign must not be removed until all work has been completed.

(Reason: Statutory requirement.)

60. NOTICE OF COMMENCEMENT (CW)

No work shall commence until the following details are submitted to Council:

- i) a Notice of Commencement (form will be attached with issue of a Construction Certificate or available from our website) within two (2) days of the date on which it is proposed to commence works associated with the Development Consent;
- ii) details of the appointment of a Principal Certifying Authority (either Council or another Principal Certifying Authority); and
- iii) details of the name, address and licence details of the Builder.

(Reason: Statutory requirement.)

CONDITIONS TO BE SATISFIED DURING DEMOLITION AND BUILDING WORKS (DW)

61. FILL MATERIAL (DW)

The only waste derived material which may be received at the development site is:

- i) Virgin excavated material (within the meaning of the Protection of the Environment Operations Act 1997), and
- ii) any other waste-derived material the subject of a resource recovery exemption under cl.51A of the Protection of the Environment Operations (Waste) Regulation 2005 that is permitted to be used as fill material.

Any (b)-type material received at the development site must be accompanied by

documentation certifying by an appropriately qualified environmental consultant the materials compliance with the exemption conditions; and this documentation must be provided to the Principal Certifying Authority on request.

(Reason: To ensure imported fill is of an acceptable standard for environmental protection purposes.)

62. OBSTRUCTION OF PUBLIC WAY NOT PERMITTED DURING WORKS (DW)

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances, without the prior approval of Council.

(Reason: To maintain public access and safety.)

63. PUBLIC INFRASTRUCTURE AND SERVICES (DW)

The applicant must comply with the requirements (including financial costs) of any relevant utility provider (e.g. Energy Australia, Sydney Water, Telstra, RMS, Council etc.) in relation to any connections, works, repairs, relocation, replacements and/or adjustments to public infrastructure or services affected by the development.

(Reason: To maintain public infrastructure and/or services.)

64. SITE REQUIREMENTS DURING DEMOLITION AND CONSTRUCTION

All of the following are to be satisfied/complied with during demolition, construction and any other site works:

- i) All demolition is to be carried out in accordance with Australian Standards AS 2601-2001.
 - ii) Demolition must be carried out by a registered demolition contractor.
 - iii) A single entrance is permitted to service the site for demolition and construction. The footway and nature strip at the service entrance must be planked out with close boarded, hardwood timber footpath protection pads. The pad shall cover the entire width of the footpath opening for the full width of the fence.
 - iv) No blasting is to be carried out at any time during construction of the building.
 - v) Care must be taken during demolition/ excavation/ building/ construction to prevent any damage to adjoining buildings.
 - vi) Adjoining owner property rights and the need for owner's permission must be observed at all times, including the entering onto land for the purpose of undertaking works.
 - vii) Any demolition and excess construction materials are to be recycled wherever practicable.
 - viii) The disposal of construction and demolition waste must be in accordance with the requirements of the Protection of the Environment Operations Act 1997.
 - ix) All waste on the site is to be stored, handled and disposed of in such a manner as to not create air pollution (including odour), offensive noise or pollution of land and/or water as defined by the Protection of the Environment Operations Act 1997.
 - x) All excavated material should be removed from the site in the approved manner and be disposed of lawfully to a tip or other authorised disposal area.
 - xi) Section 143 of the Protection of the Environment Operations Act 1997 requires waste to be transported to a place which can lawfully accept it. All non-recyclable demolition materials are to be disposed of at an approved waste disposal depot in accordance with legislation.
 - xii) All materials on site or being delivered to the site are to generally be contained within
-

the site. The requirements of the Protection of the Environment Operations Act 1997 must be complied with when placing/stockpiling loose material, disposing of concrete waste, or other activities likely to pollute drains or water courses.

- xiii) Details as to the method and location of disposal of demolition materials (weight dockets, receipts etc.) should be kept on site as evidence of approved methods of disposal and recycling.
- xiv) Any materials stored on site must be stored out of view or in such a manner so as not to cause unsightliness when viewed from nearby lands or roadways.
- xv) Public footways and roadways adjacent to the site must be fully maintained and cleared of obstructions during construction unless prior separate approval from Council is obtained including payment of relevant fees.
- xvi) Building operations such as brick cutting, washing tools or paint brushes, and mixing mortar not be performed on the roadway or public footway or any other locations which could lead to the discharge of materials into the stormwater drainage system.
- xvii) All site waters during excavation and construction must be contained on site in an approved manner to avoid pollutants entering into waterways or Council's stormwater drainage system.
- xviii) Stamped plans, specifications, documentation and the consent shall be available on site at all times during construction.

(Reason: To ensure that demolition, building and any other site works are undertaken in accordance with relevant legislation and policy and in a manner which will be non-disruptive to the local area.)

65. **SURVEY REPORT OF APPROVED LEVELS DURING AND POST CONSTRUCTION (DW)**

A Survey Certificate to Australian Height Datum shall be prepared by a Registered Surveyor as follows:

- i) At the completion of the first structural floor level prior to the pouring of concrete indicating the level of that floor and the relationship of the building to the boundaries.
- ii) At the completed height of the building, prior to the placement of concrete form work, or the laying of roofing materials.
- iii) At the completion of the development.

Progress certificates in response to points (1) through to (3) shall be provided to the Principal Certifying Authority at the time of carrying out relevant progress inspections. Under no circumstances is work allowed to proceed until such survey information is submitted to and approved by the Principal Certifying Authority.

(Reason: To ensure compliance with the approved plans.)

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE (OC)

66. **CAR PARKING - SURPLUS VEHICULAR CROSSINGS (OC)**

All surplus vehicular crossings and/or kerb laybacks must be removed and reinstated with concrete kerb and gutter or to the existing edging profile as specified by Council. The nature strip is to be restored and the footpath area reinstated. All of the above are to be restored to the satisfaction of Council's Engineer and at full cost to the applicant, prior to the issue of any Occupation Certificate.

(Reason: Maintenance of public infrastructure.)

67. **CAR PARKING - VISITOR CAR PARKING SIGNAGE (OC)**

A sign shall be erected in a suitable location on the property near the driveway entrance indicating where visitor parking is available on the site. Signage shall also be erected above the visitor parking itself. Details demonstrating compliance shall be demonstrated to the Principal Certifying Authority, prior to the issue of any Occupation Certificate.

(Reason: Adequate access and egress.)

68. ENGINEERING WORKS (CERTIFICATION OF)

Prior to occupation of the premises, a Work As Executed (WAE) Plan of all engineering and/or drainage works is to be submitted to the Principal Certifying Authority. The WAE Plan is to be certified by a suitably Qualified Engineer, with Corporate Membership standing in the Institution of Engineers Australia and registered on the National Professional Engineers Register (NPER) under the appropriate professional category, demonstrating that:

- i) the stormwater drainage system; and/or
- ii) the car parking arrangement and area; and/or
- iii) any related footpath crossing works; and/or
- iv) the proposed basement pump and well system; and/or
- v) the proposed driveway and layback; and/or
- vi) any other civil works

have been constructed in accordance with the approved plans and any relevant Standards and Council policies/specifications.

For major works, such as subdivisions, works within the road reserve (requiring separate S138 approval) and as where specified by Council, a Part 4A Certificate will be required. It is strongly recommended that an Engineer supervise all engineering related works.

Where Council is not the Principal Certifying Authority, an electronic copy of the above documents is to be provided to Council, prior to the issue of any Occupation Certificate.

(Reason: Asset management.)

69. LANDSCAPING - ARBORIST'S FOLLOW UP REPORT OF TREE/S TO BE RETAINED (OC)

As part of the on-going assessment of the tree/s to be retained, the consulting arborist engaged by the applicant is to assess their health and any impacts suffered by them as a result of the proposed approved development, prior to the issue of an Occupation Certificate. Findings are to be compiled in a detailed report and submitted to the Principle Certifying Authority, which documents the following:

- i) methods of excavation or construction used to carry out the works;
- ii) any damage sustained by the tree/s as a result of the works;
- iii) any subsequent remedial works required to be carried out by the consulting arborist as a result of the damage; and
- iv) any future or on-going remedial work required to be carried out to ensure the long term retention of the tree/s.

(Reason: To ensure the survival of trees to be retained.)

70. OCCUPATION OF BUILDING (OC)

A person must not commence occupation or use (or change of use where an existing building) of the whole or any part of a new building (within the meaning of section 109H (4) of the Act) unless an Interim Occupation Certificate or Final Occupation Certificate has been issued in relation to the building or part.

The Principal Certifying Authority is required to be satisfied, amongst other things, that:

- i) all required inspections (including each applicable mandatory critical stage inspection) have been carried out; and
- ii) any preconditions to the issue of the certificate required by a development consent have been met.

Note: New building includes an altered portion of, or an extension to, an existing building.

(Reason: Statutory requirement.)

71. STORMWATER - CERTIFICATION OF THE CONSTRUCTED DRAINAGE SYSTEM (OC)

The constructed stormwater system shall be certified by a suitably qualified person, in accordance with Council's Stormwater Management Code, prior to the issue of any Occupation Certificate.

(Reason: Adequate stormwater management.)

72. STORMWATER - COVENANT AND RESTRICTION AS TO USER FOR STORMWATER CONTROLLED SYSTEMS (OC)

Prior to the issue of any Occupation Certificate, the applicant shall register a Positive Covenant and a Restriction as to User under section 88E and or section 88B of the Conveyancing Act as appropriate in favour of Council, ensuring the ongoing retention, maintenance and operation of the stormwater facility (on-site detention)

Where any drainage line or service conduit is to traverse any property other than that which it serves, an appropriate easement will be required. In this case, the applicant shall register an easement no less than 1200mm wide over the proposed drainage line or service concurrently with any subdivision registration.

The wording on the 88B Instrument is to make reference to the Council file where the Construction plans and the Work As Executed (as built), plans are held. Typical wording can be obtained from Council's Specification for the Management of Stormwater document.

(Reason: To ensure the on-site detention and/or pump system is maintained to an appropriate operational standard.)

CONDITIONS TO BE SATISFIED DURING ONGOING USE OF THE PREMISES (OU)

73. BOARDING HOUSES - OPERATIONAL PLAN OF MANAGEMENT (OU)

An Operational Plan of Management is to be formulated and submitted to Council for approval, prior to the issue of any Occupation Certificate.

The Plan of Management must include the minimum criteria as stipulated in Schedule 2 (Standards for Places of Shared Accommodation) of the Local Government (General) Regulation, 2005 under the Local Government Act 1993, the Public Health Act, 1991, Boarding Houses Act 2012 and Boarding Houses Regulation 2013.

The plan shall be dated and the name and signature of the author of the document shall be included. The Plan of Management shall be displayed in prominent locations within the premises and a copy of the Plan shall be provided to all residents of the boarding house. The on-site Caretaker shall be responsible for ensuring that the terms of the Plan are adhered to at all times.

This Operational Plan of Management must incorporate the following:

- i) All the measures to be implemented on the premises in terms of safety & security, amenity and health including but not limited to matters relating to curfews and after-hours access, bringing of visitors on to the site, drug and alcohol policy (including smoking), and use of communal areas etc.
- ii) All the responsibilities of the Caretaker/Manager.
- iii) An Incident Register to be maintained by the Caretaker. This Register must be produced upon demand by any Council officer or NSW Police Officer. The Register must contain a direction that all incidents of a criminal nature are to be reported to the Police immediately.
- iv) Prior to commencement of the boarding house use, a notification letter shall be forwarded to Council, the Police and neighbours providing contact details for the Caretaker/Manager so that any issues regarding the operation of the premises etc. can be addressed promptly. Evidence of this letter being forwarded as required in this condition shall be provided to the Principal Certifying Authority, prior to the issue of any Occupation Certificate and commencement of the use.

The Plan of Management referred to in this condition shall be reviewed by Council annually from the date of issue of an Occupation Certificate by the Principal Certifying Authority. The operator of the boarding house shall contact Council annually to carry out this review and the review shall include the Incident Register referred to in point (iii) above. Should amendments be made to the Plan of Management an updated version of same shall be provided to Council and the residents of the boarding house within one (1) month of the annual review being completed.

(Reason: To minimise the impact of the use on surrounding residences.)

74. **BOARDING HOUSE - ONGOING USE OF (OU)**

Ongoing operation of the approved use for the purpose of a boarding house shall comply with the following:

- i) Use of the premises shall remain consistent with the definition of 'boarding house' as defined under Strathfield Local Environmental Plan 2012 as a building that:
 - is wholly or partly let in lodgings, and
 - provides lodgers with a principal place of residence for 3 months or more, and
 - may have shared facilities, such as a communal living room, bathroom, kitchen or laundry, and
 - has rooms, some or all of which may have private kitchen and bathroom facilities, that accommodate one or more lodgers but does not include "backpackers" accommodation, a group home, a serviced apartment, seniors housing or hotel or motel accommodation.
 - ii) Subdivision of the approved boarding house under strata or community title is prohibited.
 - iii) The use and operation of the boarding house shall comply with all applicable legislation/regulation and standards, including:
 - Boarding Houses Act 2012;
 - Boarding Houses Regulation 2013;
-

- Local Government Act 1993; and
 - Schedule 2 (Standards for Places of Shared Accommodation) of the Local Government (General) Regulation 2005.
- iv) **The Boarding house is required to be registered on a register administered by NSW Fair Trading.**
- v) The maximum number of persons accommodated in a bedroom, or in a cubicle of a dormitory, must not exceed the number determined by allowing a minimum floor area within the bedroom or cubicle in accordance with the relevant provisions under the Public Health Act 1991 for each person.
- vi) No speakers or music is permitted outdoors or in the communal areas

(Reason: To minimise the impact of the boarding house on surrounding residences.)

75. NOISE - COMPLIANCE WITH ACOUSTIC ASSESSMENT REPORT (OU)

All recommendations contained in the approved Acoustic Assessment Report Acouras Consultancy – 15 October 2017 shall be adopted, implemented, and adhered to.

The Principal Certifying Authority (PCA) shall obtain a statement from an appropriately qualified acoustic consultant, certifying that the acoustic mitigation measures outlined in the above stated report have been suitably incorporated into the development and that relevant noise criteria have been satisfied prior to the issue of any Occupation Certificate.

Any changes made to the proposal that would alter the acoustic assessment will require a further acoustic assessment and a copy of this further report shall be provided to Council for approval prior to the commencement of works and any recommendations adopted, implemented, and adhered to.

(Reason: Noise control and amenity.)

76. NOISE - NO AMPLIFIED MUSIC (OU)

Music and other amplified sound played on the premises shall not give rise to offensive noise as defined under the provisions of the Protection of the Environment Operations Act 1997. The sound level output shall not exceed 5 dB(A) above the ambient background level at the received boundary.

Speakers must not be installed and music must not be played in any of the outdoor areas associated with the premises including the public domain. Speakers located within the premises must not be placed so as to direct the playing of music towards the outdoor areas associated with the premises.

(Reason: Environmental amenity.)

RESOLUTION

The Panel recommends to the General Manager or his nominee that this item be **APPROVED** subject to the addition of recommended **Special Condition 3A** and amendment to **General Condition 74**.

FOR: P.Stein, B.Kirk, V.Albin, P.Smith

AGAINST: Nil

**** End Minutes - Report No. 4****